

Support WiFi and Bluetooth 80mm Mini Portable Thermal Receipt Printer

(M/N:OCP-P-M085)

Products Features

1. Business style design, more fashion
2. Support 1D,2D bar code printing
3. While compatible with Windows, Linux, Android and IOS systems
4. With 2500mAh rechargeable lithium polymer battery,super battery lasting time, with smart power saving and power consumption control functions , to ensure longer print time
5. Support USB+COM +Bluetooth or USB+COM+Bluetooth+WIFI,
6. Special power remaining indicator light, to control the printer power at any time
7. Support sound and light reminder when lack of paper or printing abnormal
8. Anti fall of 1.5M cement floor

Application:

Warehousing, transportation, logistics, supermarket, tobacco, hydropower reading, mobile government affairs, mobile police, postal and other industries

Parameters

Item	Parameter
Print parameter	Printing Method Thermal Line
	Effective Printing Width 72mm
	Resolution 576 dots/line[8dots/mm][203dpi]
	Printing Speed 90mm/s
	Interface USB (standard USB2.0 communication protocol, support Windows, Linux, Android, IOS) Bluetooth (Bluetooth2.0, Bluetooth3.0+4.0, support Android, IOS) WIFI (2.4GHz, ATA, AP, ATA+AP mode)
	Line spacing 3.75mm[Can adjust line spacing by command]
	Line No. Font A:48 character /Line Font B:64 character/Line Simple,traditional Chinese-24 lines
	Character The standard GB18030 simplified / traditional Chinese characters library
	Character Size ANK character[Font A][1.5x3.0mm][12x24 dots] Font B[1.1x2.1mm][9x17 dots] Simplified/Traditional[3.0x3.0mm][24x24dots]
	Extended character set PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iranli/Latvian/Arabic/PT151.1251/WPC1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151.1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Bar code character	Bar code 1D,Bar code[UPC-A/UPC-E/JAN13(EAN13)]/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128 2D,Bar code[QR CODE]
Graphics printing	Graphics printing Supports bitmap download and print
Power saving Mode	Smart power saving Support
	Variable speed printing Support
	Consumption Support
	Dormancy Support
Dection Indicator	Sensor Lack of paper detection
	Power Display Support
	Charge Indicator Support
	Lack of paper Support
Paper	Beep Lack of paper,printing abnormal alarm
	Type Thermal
	Width 79.5±0.5mm
	thickness ≤0.12mm
	Diameter ≤40mm
	Feed Easy[Clamshell feed]
Print commands	Commands ESC/POS
	Type Rechargeable Lithium polymer battery
	Capacity 2500mAh/7.4V, can be charged more than 800 times sustainable printing 150 meters or 4 hours under normal use
	Charger 9.0V/2A
Buffer	Input 4KB
	NV Flash 40KB
Physical features	Weight 285G
	Dimension 114*103*50(MM)
Environment	Operating Temp:[5 ~ 45℃] Humidity:[10 ~ 80%]
	Storage Temp:[-10 ~ 50℃] Humidity:[10 ~ 90%/No Dew]
Reliability	Print head life 50KM[Printing Density:12.5]
Software	Driver Android,IOS, Linux, WinXP,Win7,Win8,Win8.1,Win10







OCPP-M085







OCPP-M085



