

# 15-inch Capacitive Touch Screen LCD POS Monitor

(Model No: TM-1501C)

## Features:



Multifunctional setting key;

5 or 4 wire touch panel for option;

Grade A LCD panel with LED backlight;

High resolution 1024\*768@60HZ;

Suitable for all kinds of high-intensity working environment.

## Specification:

|          |   |
|----------|---|
| Model    | TM-1501C  |
| Name     | 15.1 inch capacitive touch screen monitor                   |
| Color    | Whole black color machine                                   |
| Material | Metal base with plastic machine body                        |
| VESA     | 75*75mm for wall mounting(need extra wall mounting bracket) |

|                           |   |
|---------------------------|---|
| OSD Language              | Support 8kinds of international languages   |
| Display                   |   |
| Display area              | 304.128(H)* 228.096(V)  |
| Pixel pitch               | 0.297*0.297   |
| Aspect ratio              | 4:3   |
| Resoluiton                | 1024*768  |
| Brightness                | 250cd/m2  |
| Contrast                  | 700:1   |
| Display color             | 16.2M   |
| View angle                | Horizon: 135; Vertical :140   |
| Response time             | 8ms   |
| Touch function            |   |
| Touch screen              | Multi-point capacitive tocuh panel  |
| Structure                 | G+G□Cover Glass+LOCA+ITO+Glass□   |
| Responding speed          | <5ms  |
| Total light transmittance | 85% above   |
| Touch life                | >50,000,000 times   |
| Connectivity              |   |
| Rear I/O                  | 12V DC in jack*1  |
|                           | USB *1 for touch function   |
|                           | 15PIN D-sub VGA *1  |
|                           | HDMI*1 for option   |
|                           | Audio in*1 for option (built in speaker for option)   |
| Side key function         | Auto, Menu,Up,Down,Power Swicth   |
| Environment               |   |
| Operating temperature     | 0 to 40 degrees centigrade  |
| Storage temperature       | -10 to 60 degrees centigrade  |
| Working humidity          | 10%~80% No condensation   |
| Storage humidity          | 10%~90% No condensation   |
| Package                   |   |
| Package with foam inside  | 430*150*420mm/6.0kg   |
| 5 in 1 carton             | 590*420*430mm/21kg  |
| Accessories               |   |
| Power adapter             | 110-240V/50-60HZ AC power input ,DC12V/2.6A output adaptor  |
| Cable                     | Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) |
| Touch related             | Touch pen   |















# Application



Bar



Restaurant



Coffee Store



Mile Tea Store



Bakery



Convenience Store



Library



Supermarket

# FACTORY STRENGTH



