17-Inch Factory OEM ODM Wholesale Touch Screen LCD Monitor with Metal Base

(Model No: TM-1701)

Features:





Multifunctional setting key;

5 or 4 wire touch panel for option;

Grade A LCD panel with LED backlight;

High resolution 1280*1024@60HZ;

Suitable for all kinds of high-intensity working environment.

Specification:

| Model | TM-1701 |
|--------------|---|
| Name | 17 inch touch screen display |
| Color | Whole black color machine usually |
| Material | Metal base with plastic body |
| VESA | 75*75mm for wall mounting(need extra wall mounting bracket) |
| OSD Language | Support 8kinds of international languages |
| Display | |
| Display area | 337.92(W)×270.336(H) mm |
| Pixel pitch | 0.264*0.264 |
| Aspect ratio | 5:4 |
| Resoluiton | 1280*1024 |

| Contrast 1000:1 107M 1 | Brightness | 300cd/m2 |
|--|--------------------------|--|
| Display color 16.7M Morzon: 150; Vertical: 150 | _ | |
| View angle Horizon: 160; Vertical: 150 Response time 5ms Touch function Touch screen 5-wire resistive touch panel. 4-wiretouch screen for option Structure ITO Film and ITO Glass FIT undrace treatment Fog surface, anti-glare Responding speed -8ms Surface hardness Pencil hardness.3H Total light transmittance 72% above Connectivity 2 w 35000000 times Connectivity 2 w 1 for touch function Rear I/O 2 % 1 for touch function Rear I/O 15PIN D sub VGA *1 w 1 w 1 w 1 w 1 w 1 w 1 w 1 w 1 w 1 | | |
| Response time 5rms Touch function 5rouch function 5rouch screen 5-wire resistive touch panel,4-wiretouch screen for option Structure 170 Film and 170 Glass FiT Surface treatment Fog surface, anti-glare Responding speed <fms *1="" 1="" 128="" 15pin="" 5-35000000="" 5-ms="" 72%="" above="" anti-glare="" connectivity="" d-10="" d-1<="" fog="" for="" function="" hardness="" hardness:3h="" i="" july="" life="" light="" o="" pencil="" rear="" responding="" speed="" surface="" surface,="" td="" times="" total="" touch="" transmittance="" treatment="" vsa="" °=""><td></td><td></td></fms> | | |
| Touch screen Swire resistive touch panel,4-wiretouch screen for option Structure TO Film and TO Glass FTT Surface treatment Fog surface, anti-glare Responding speed <8ms Surface hardness Pencil hardness:3H Total light transmittance 72% above Touch life >35000000 times Connectivity 12V DC in jack*1 USB *1 for touch function Rear I/O 15PND >ub VGA *1 HDM*1 for option Audio in*1 for option (built in speaker for option) Side key function Auto, Menu, Up, Down, Power Switch Environment Operating temperature O to 40 degrees centigrade Storage temperature 10 to 60 degrees centigrade Storage hamidity 10%-80% No condensation Package Package Package Package Workson 10240V50-60HZ AC power input, DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available, USB cable for touch, VGA cable(HDMI cable for option) Couch related Touch pen,driver disk | | |
| Touch screen Sewire resistive touch panel,4-wiretouch screen for option | | |
| Structure | | |
| surface treatment Fog surface, anti-glare Responding speed <8ms Surface hardness Pencil hardness:3H Total light transmittance 72% above Touch life >35000000 times Connectivity 2V DC in jack*1 USB *1 for touch function Rear I/O 15PIN D-sub VGA *1 HDMI*1 for option Auto, Menu Up, Down, Power Switch Environment Description (built in speaker for option) Side key function Auto, Menu Up, Down, Power Switch Environment Operating temperature 0 to 40 degrees centigrade Storage temperature 10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-80% No condensation Storage with foam inside 445*18xm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power card compatible with USA /EU / UK etc and customized available.USB cable for touch, VGA cable(HDMI cable for option) Otoch related Touch pen, driver disk | | |
| Responding speed <8ms | | |
| Surface hardness Pencil hardness:3H Total light transmittance 72% above Touch life >35000000 times Connectivity | | |
| Total light transmittance Touch life >35000000 times Connectivity 12V DC in jack*1 USB *1 for touch function 15PIN D-sub VGA *1 14DMI*1 for option Audio in*1 for option (built in speaker for option) Side key function Audio in*1 for option (built in speaker for option) Side key function Audio in*1 for option (built in speaker for option) Side key function Audio in*1 for option (built in speaker for option) Side key function Audio in*1 for option (built in speaker for option) Storage temperature 0 to 40 degrees centigrade Operating temperature 10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Touch pen,driver disk Touch pen,driver disk Touch related Touch pen,driver disk To | | |
| Touch life >3500000 times Connectivity 12V DC in jack*1 12V DC in | | |
| Connectivity Rear I/O Rear I/O Rear I/O Auto in*1 for option (built in speaker for option) Side key function Auto in*1 for option (built in speaker for option) Side key function Auto, Menu, Up, Down, Power Swicth Environment Operating temperature Oto 40 degrees centigrade Storage temperature -10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-80% No condensation Storage with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK et and customized available, USB cable for touch, VGA cable(HDMI cable for option) Touch related Other | | |
| Rear I/O To to be the form of the form | | >35000000 times |
| Rear I/O SPIN D-sub VGA *1 HDM**1 for option (built in speaker for option) Audio in**1 for option (built in speaker for option) Auto, Menu, Up, Down, Power Swicth | Connectivity | |
| Rear I/O SiPIN D-sub VGA *1 | Rear I/O | 12V DC in jack*1 |
| HDMI*1 for option Audio in*1 for option (built in speaker for option) Side key function Auto, Menu,Up,Down,Power Swicth Environment Operating temperature 0 to 40 degrees centigrade Storage temperature -10 to 60 degrees centigrade Working humidity 10%~80% No condensation Storage humidity 10%~90% No condensation Package Package with foam inside 445*180*415mm/8.0kg 4in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | | USB *1 for touch function |
| Audio in*1 for option (built in speaker for option) Side key function Auto, Menu,Up,Down,Power Swicth Environment Operating temperature 0 to 40 degrees centigrade Storage temperature -10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package Package Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | | 15PIN D-sub VGA *1 |
| Side key function Auto, Menu, Up, Down, Power Swicth Environment Operating temperature 0 to 40 degrees centigrade Storage temperature -10 to 60 degrees centigrade Working humidity 10%~80% No condensation Storage humidity 10%~90% No condensation Package Package | | HDMI*1 for option |
| Environment Operating temperature Ot o 40 degrees centigrade Storage temperature 10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Other | | Audio in*1 for option (built in speaker for option) |
| Operating temperature | Side key function | Auto, Menu,Up,Down,Power Swicth |
| Storage temperature -10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package Package 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | Environment | |
| Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package Package 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | Operating temperature | 0 to 40 degrees centigrade |
| Storage humidity 10%~90% No condensation Package Package 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | Storage temperature | -10 to 60 degrees centigrade |
| Package Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Other | Working humidity | 10%-80% No condensation |
| Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | Storage humidity | 10%~90% No condensation |
| 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | Package | |
| Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | Package with foam inside | 445*180*415mm/8.0kg |
| Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | 4 in 1 carton | 630*450*430mm/25kg |
| Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other | Accessories | |
| Touch related Touch pen,driver disk Other | Power adapter | 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor |
| Other Control | Cable | Power cord compatible with USA /EU / UK etc and customized available, USB cable for touch, VGA cable (HDMI cable for option) |
| | Touch related | Touch pen,driver disk |
| Certification CE,ROHS,CCC,FCC | Other | |
| | Certification | CE,ROHS,CCC,FCC |

























