17 Inches Grade-a 5 or 4 Wire Touch Panel POS Touch Screen Monitor with Metal Base

(Model No: TM-1701)

Features:





Multifunctional setting key;

5 or 4 wire touch panel for option;

Grade A LCD panel with LED backlight;

High resolution 1280*1024@60HZ;

Suitable for all kinds of high-intensity working environment.

Specification:

Model	TM-1701
Name	17 inch touch screen display
Color	Whole black color machine usually
Material	Metal base with plastic body
VESA	75*75mm for wall mounting(need extra wall mounting bracket)
OSD Language	Support 8kinds of international languages
Display	
Display area	337.92(W)×270.336(H) mm
Pixel pitch	0.264*0.264
Aspect ratio	5:4
Resoluiton	1280*1024

Contrast 1000:1 107M 1	Brightness	300cd/m2
Display color 16.7M Morzon: 150; Vertical: 150	_	
View angle Horizon: 160; Vertical: 150 Response time 5ms Touch function Touch screen 5-wire resistive touch panel. 4-wiretouch screen for option Structure ITO Film and ITO Glass FIT undrace treatment Fog surface, anti-glare Responding speed 4-8ms Surface hardness Pencil hardness.3H Total light transmittance 72% above Connectivity 2.2 b		
Response time 5rms Touch function 5rouch function 5rouch screen 5-wire resistive touch panel,4-wiretouch screen for option Structure 170 Film and 170 Glass FiT Surface treatment Fog surface, anti-glare Responding speed <fms *1="" 1="" 128="" 15pin="" 5-35000000="" 5-ms="" 72%="" above="" anti-glare="" connectivity="" d-10="" d-1<="" fog="" for="" function="" hardness="" hardness:3h="" i="" july="" life="" light="" o="" pencil="" rear="" responding="" speed="" surface="" surface,="" td="" times="" total="" touch="" transmittance="" treatment="" vsa="" °=""><td></td><td></td></fms>		
Touch screen Swire resistive touch panel,4-wiretouch screen for option Structure TO Film and TO Glass FTT Surface treatment Fog surface, anti-glare Responding speed <8ms Surface hardness Pencil hardness:3H Total light transmittance 72% above Touch life >35000000 times Connectivity 12V DC in jack*1 USB *1 for touch function Rear I/O 15PND >ub VGA *1 HDM*1 for option Audio in*1 for option (built in speaker for option) Side key function Auto, Menu, Up, Down, Power Switch Environment Operating temperature O to 40 degrees centigrade Storage temperature 10 to 60 degrees centigrade Storage hamidity 10%-80% No condensation Package Package Package Package Workson 10240V50-60HZ AC power input, DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available, USB cable for touch, VGA cable(HDMI cable for option) Couch related Touch pen,driver disk		
Touch screen Sewire resistive touch panel,4-wiretouch screen for option		
Structure		
surface treatment Fog surface, anti-glare Responding speed <8ms Surface hardness Pencil hardness:3H Total light transmittance 72% above Touch life >35000000 times Connectivity 2V DC in jack*1 USB *1 for touch function Rear I/O 15PIN D-sub VGA *1 HDMI*1 for option Auto, Menu Up, Down, Power Switch Environment Description (built in speaker for option) Side key function Auto, Menu Up, Down, Power Switch Environment Operating temperature 0 to 40 degrees centigrade Storage temperature 10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-80% No condensation Storage with foam inside 445*18xm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power card compatible with USA /EU / UK etc and customized available.USB cable for touch, VGA cable(HDMI cable for option) Otoch related Touch pen, driver disk		
Responding speed <8ms		
Surface hardness Pencil hardness:3H Total light transmittance 72% above Touch life >35000000 times Connectivity		
Total light transmittance Touch life >35000000 times Connectivity 12V DC in jack*1 USB *1 for touch function 15PIN D-sub VGA *1 14DMI*1 for option Audio in*1 for option (built in speaker for option) Side key function Audio in*1 for option (built in speaker for option) Side key function Audio in*1 for option (built in speaker for option) Side key function Audio in*1 for option (built in speaker for option) Side key function Audio in*1 for option (built in speaker for option) Storage temperature 0 to 40 degrees centigrade Operating temperature 10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Touch pen,driver disk Touch pen,driver disk Touch related Touch pen,driver disk To		
Touch life >3500000 times Connectivity 12V DC in jack*1 12V DC in		
Connectivity Rear I/O Rear I/O Rear I/O Auto in*1 for option (built in speaker for option) Side key function Auto in*1 for option (built in speaker for option) Side key function Auto, Menu, Up, Down, Power Swicth Environment Operating temperature Oto 40 degrees centigrade Storage temperature -10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-80% No condensation Storage with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK et and customized available, USB cable for touch, VGA cable(HDMI cable for option) Touch related Other		
Rear I/O To to be the form of the form		>35000000 times
Rear I/O SPIN D-sub VGA *1 HDM**1 for option (built in speaker for option) Audio in**1 for option (built in speaker for option) Auto, Menu, Up, Down, Power Swicth	Connectivity	
Rear I/O SiPIN D-sub VGA *1	Rear I/O	12V DC in jack*1
HDMI*1 for option Audio in*1 for option (built in speaker for option) Side key function Auto, Menu,Up,Down,Power Swicth Environment Operating temperature 0 to 40 degrees centigrade Storage temperature -10 to 60 degrees centigrade Working humidity 10%~80% No condensation Storage humidity 10%~90% No condensation Package Package with foam inside 445*180*415mm/8.0kg 4in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other		USB *1 for touch function
Audio in*1 for option (built in speaker for option) Side key function Auto, Menu,Up,Down,Power Swicth Environment Operating temperature 0 to 40 degrees centigrade Storage temperature -10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package Package Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other		15PIN D-sub VGA *1
Side key function Auto, Menu, Up, Down, Power Swicth Environment Operating temperature 0 to 40 degrees centigrade Storage temperature -10 to 60 degrees centigrade Working humidity 10%~80% No condensation Storage humidity 10%~90% No condensation Package Package		HDMI*1 for option
Environment Operating temperature Ot o 40 degrees centigrade Storage temperature 10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Other		Audio in*1 for option (built in speaker for option)
Operating temperature	Side key function	Auto, Menu,Up,Down,Power Swicth
Storage temperature -10 to 60 degrees centigrade Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package Package 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other	Environment	
Working humidity 10%-80% No condensation Storage humidity 10%-90% No condensation Package Package 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other	Operating temperature	0 to 40 degrees centigrade
Storage humidity 10%~90% No condensation Package Package 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other	Storage temperature	-10 to 60 degrees centigrade
Package Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Other	Working humidity	10%-80% No condensation
Package with foam inside 445*180*415mm/8.0kg 4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other	Storage humidity	10%~90% No condensation
4 in 1 carton 630*450*430mm/25kg Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other	Package	
Accessories Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other	Package with foam inside	445*180*415mm/8.0kg
Power adapter 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other	4 in 1 carton	630*450*430mm/25kg
Cable Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) Touch related Touch pen,driver disk Other	Accessories	
Touch related Touch pen,driver disk Other	Power adapter	110-240V/50-60HZ AC power input ,DC12V/4A output adaptor
Other Control	Cable	Power cord compatible with USA /EU / UK etc and customized available, USB cable for touch, VGA cable (HDMI cable for option)
	Touch related	Touch pen,driver disk
Certification CE,ROHS,CCC,FCC	Other	
	Certification	CE,ROHS,CCC,FCC

























