

Tabletop Square 2D Barcode Reader

(Model No: OCBS-2103)

PRODUCT FEATURES:

Focus on the 1D/2D symbologies on the screen of mobile phone;
Well designed on the light source to meet all kinds of high bright;
Low resolution mobile LED/LCD screen barcodes scanning.

PRODUCT SPECIFICATION:

Performance Characteristics		
Microprocessor		IOTC 0370 CHIP
Resolution		640×480 CMOS
Interface		RS-232 (9.6~115.2Kbps), USB 1.1 (HID-KBW, HID-POS)
Symbologies	2D	PDF417, Data Matrix, QR code
	1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Coda bar, Code 128(Include FNC1 FNC2 FNC3 subset), Code 93, ITF-6, ITF-14, Interleaved 2 of 5,Industrial 2 of 5, Standard 2 of 5, Matri 2 of 5, GS1 Data bar (RSS-Expand, RSS-Limited, RSS-14),Code 39(Include Code 39 FULL ASCII),Code 11,MSI-Plessey
Precision		≥ 10 mil
Light Source		White LED
Scanning model		sense scanning, continuous scanning
Precision		10 mil
Print Contrast Signal		≥ 30%
Filed angel		Diagonal: 68°, Horizontal: 42°, Vertical: 54°
Illumination		0 ~ 100,000 LUX
Power Consumption		1 W
Voltage		DC 5V, 0.5A□AC 100~240V, 50~60Hz
Result feedback		Buzzer, Indicator light
Dimension		127.3mm(L) X 111.5mm (W) X 94mm(H)
Weight		300 g
Environment		
Operate Temperature		-10℃ to + 50℃
Storage Temperature		-20℃ to + 60℃
Humidity		5% - 95%□non-condensing□
Programming Software		Quick Set, Programming Guide, uTools Lite
Certification		FCC Part15 Class B, CE EMC Class B