## 15.6 or 15.1 Inch All In One Touch POS Terminal

(M/N:POS-H156W/A-H151W/A)



OCOM H series pos integrated high speed thermal printer and scanner module inside, it is a kind of cost-effective machine for using, different frame colors make machine more beautiful ,extended IO interface make a few more external devices connected, newly designed rear cover which can be easily removed without tools for faster installation and maintenance

Features:

Intel Celeron series and intel core I3 I5 processor for option

Rockchip high speed RK3288 processor

EMMC 8GB/16GB/32GB for option

Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for option

58mm and 80mm high speed thermal printer built in for option

Multi-point projected capacitive touch panel

Optional side MSR and VFD220 customer display mounted to back cover

Bar-code scanner inbuilt for option

True flat and water-proof/scratch-resistant sureface display

Specification

Name15.6 inch all in one touch screen pos terminal15.1 inch all in screen pos terHousingplastic with metal combinedColorwhite machine body or black machine body r orange or blue frame colorsDisplay15.6 inch touch screen	rminal	
Color white machine body or black machine body i orange or blue frame colors Display		
orange or blue frame colors Display		
	ch screen	
Main corport	ch screen	
Main screen 15.6 inch touch screen 15.1 inch touc monitor monitor		
Resolution 1366*768 1024*768		
Brightness 250cd/m <sup>2</sup>		
View angle Horizon: 150; Vertical :140		
Touch screen Multi-point projected G+G capacitive touch		
Sub-display15.6/14/11.6 inch display W/ or W/o touch function, resolution 1366*768 for optional15.1 inch disp 	nction,	
Customer display 2*20 VFD mounted to back cover for option	2*20 VFD mounted to back cover for option	
performance		
WindowsMotherboardIntel Celeron Bay Trail J1900 2.0GHz or inteJ19004th generation CPU for option	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 $4^{th}$ generation CPU for option	
System Memory 1*SO-DIMM DDRIII slot, support1333*/1600 2GB/4GB/8GB for option	1*SO-DIMM DDRIII slot, support1333*/1600 2GB/4GB/8GB for option	
Storage device Msata SSD 64GB or higer, up to 256GB	Msata SSD 64GB or higer, up to 256GB	
Audio On board Real Tek ALC662 audio chip	On board Real Tek ALC662 audio chip	
LAN 10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded W	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	
Operating System Windows7/8/10, Embedded,WEPOS,Linux		
	Rockchip series RK3288 ,quad core 1.8G, RK3399 for optional	
System Memory On board DDRIII 2GB,4GB for option		
Storage device On board 16GB EMMC,32GB for option		
Audio On board Real Tek ALC5640 audio chip	On board Real Tek ALC5640 audio chip	
LAN 10/100Mbs,Realtek RTL8111F Lan chip	10/100Mbs,Realtek RTL8111F Lan chip	
WIFI&BT module Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 supp	Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support	
Operating System Android 7.1		
Connectivity		
Windows/Android(J1900&RK3288) power button*1		
12V DC in jack*1		
LAN:RJ-45*1		
USB *6		
MIC in*1, Audio out*1		
Windows(J1900) COM(RS232) *1 or HDMI*1 for option		
VGA(15Pin D-sub)*1		
RJ11 for Cash drawer *1 for option		

Android(RK3288)	COM(RS232) *1
	On board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional)
	TF card slot*1
Options	
80mm thermal printer	direct thermal printing
	100mm/s pringting speed
	79.5-/+ 0.5mm paper width and printable width 72mm
	with atuo cutter function and thermal head life 50km
	LPT communication
58mm thermal printer	direct thermal printing
	85mm/s pringting speed
	57.5-/+ 0.5mm paper width and printable width 48mm
	thermal head life 50km
	LPT communication
MSR	optional side MSR
Web camera	web camera mounted on top of the display for option
Scanner	support 1D&2D code-scanning for option
Speaker	4ohm/5w speakers inside for option
Package	package
Weight	net[]5.6Kg , gross:7.7Kg for 15.6 with15.6 dual screen /no printer built in
Package with foam inside	340*450*480mm
2in1 carton	700*460*500mm /gross[]17Kg
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80%
Storage humidity	10%~90%
Accessories	
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine DC12V/7A out put adaptor only for W/ 80mm printer machine
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside for option
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC

More product pictures shown



No need tools to remove the back cover , much conveniently for upgrading RAM/SSD by and service ability by customers



Side USB ports make machine more easily uploading and downloading



external IO ports



## Package









