

**USB Laser Barcode Scanner With Stand  
(Model: OCBS-LA11)**

**SPECIFICATIONS:**

<b>Performance Characteristics</b>	
<b>Light Source:</b>	Visible laser (650-670nm)
<b>Scan Rate:</b>	200 scans per second
<b>Reading Distance</b>	2.5 ~600mm (100% UPC/EAN)
<b>Scanner Type:</b>	Bi-directional
<b>Resolution:</b>	0.10mm (4mil) at PCS 0.9
<b>Print Contrast Minimum:</b>	30%, minimum reflective difference (@650nm)
<b>Error Rate:</b>	1/3000000
<b>Decode Capability:</b>	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
<b>Physical Characteristics</b>	
<b>Interfaces Supported:</b>	PS2, RS232, USB
<b>Voltage:</b>	DC+5V+/-5%
<b>Current:</b>	100 mA
<b>Idle Current:</b>	<40 mA
<b>Power Source:</b>	Host power or external (RS232) power supply
<b>Scanning Angle</b>	Inclination 45° Elevation 60°
<b>Dimensions:</b>	L165mm X W63mm X H87mm
<b>Weight:</b>	129g (without stand)
<b>Stand</b>	Optional
<b>Color:</b>	Grey and black
<b>User Environment</b>	
<b>Operating Temperature:</b>	0°C~40°C
<b>Storage Temperature:</b>	-40°C~ 60°C
<b>Humidity:</b>	5~95% relative humidity, non-condensing
<b>Electrostatic Discharge:</b>	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
<b>Drop Specifications:</b>	Withstands multiple 1.5m drops to concrete
<b>Safe:</b>	
<b>EMI/RFI:</b>	FCC Class A and CE
<b>Laser Safety:</b>	CDRH class 2 laser product

**Product Details:**



# OCBS-LA11





OCBS-LA11







OCBS-LA11





**Relevant documents:**

Do you want to know more product information? Please Click here.

[Specification](#)  
[User's Manual](#)