

20X2Characters Double Line VFD Customer Display

(Model No.:VFD220C)

Features:

- 1 Doublelines 20*2 characters VFD display;
- 1 Support26 countries languages;
- 1 Poleheight is adjustable;
- 1 360degree rotation angle;
- 1 SupportsESC/POS and CD5220 command
- 1 3kinds of different height for you choose

Specifications:

- 1 Highbrightness Vacuum Fluorescent Display for excellent visibility over a wideviewing angle.
- 1 Availablein 9mm high characters.
- 1 40characters in 20 columns by 2 lines format.
- 1 Thirteensets of international characters, plus one set of user defined charactersallows total flexibility in display fonts.
- 1 Easyprogramming using Escape sequence commands.
- 1 Emulationof Aedex, Epson and DSP800 command sets.
- 1 Displaycan swivel and tilt to a wide range of angles.
- 1 Adjustabledisplay height.
- 1 Powermay be sourced from system, with the bracket and cable kit supplied in typicalconfiguration.
- 1 ACadaptors in various configurations for all AC voltages.

Frame color	Black / white/Cyan
Display Color	Blue-Green
Display Method	Vacuum Fluorescent Display
Display Mode	2lines*20characters
Brightness	700cd/m2
Character type	96 alphanumeric,26Kinds of international character set
Character font	5X7 Dot matrix
Character size	6.75mm x 3.75mm
Dot Size	0.8 x 0.55 mm
Code page	20 Code page
Viewing Area	-5~60°
Panel Dimension	204(W)*67(H)*40(D)
Viewing Angle	188mm(L)×40mm□W□
Horizontal Rotation	Max 350°
Weight	0.9KG
Commands Mode	ESC/POS/CD5220/DSP800/UTC.....

Language Support	US English, UK English, Turkish, Bosnia, Croatian, Czech, Danish, Dutch, Estonian, Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish, Swedish...
Interface	RS232 (serial) or USB
Baudrate	2400/9600 BPS,
MTBF	40,000 hours
Power supply	DC5V 1A
Certificate	CE,ROHS,FCC



ocom
At your side

VFD220C



www.ocominc.com

CE FCC



