

Display

- * Supports 11 command modes included EPSON etc.
- * Power supply from 5V to 24V to prevent any mindless use of improper power input.
- * 20-column x 2-line dot matrix in a wide viewing angle.
- * Easy connectivity to a wide range of POS products.
- * OPOS/JPOS driver is standard.

Specification

General	Display Method	Vacuum Fluorescent Display (Blue-green)
	Number of characters	40(20 columns x 2 lines)
	Brightness	500~1000 cd/m ²
	Character font	5 x 7 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	5.25 (W) x 9.02 (H)mm
	Dot Size (X x Y)	0.86 x 1.05mm
	Download characters	9 characters
	Panel Dimension	220(W) x 45(D) x 125(H)mm
	Pole Dimension	Per support length: 140(L) x 34.5(Dia)mm
	Base Dimension	205(W) x 106(D) x 33(H)mm
	Viewing Angle	Max. 90°
	Horizontal Rotation	Max. 355°
Weight	Approx. 980 grams	
Commands Mode	LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL	
Language Support	FRANCE □ GERMANY □ U.K □ DENMARK □ SWEDEN □ ITALY □ SPAIN □ JAPAN □ NORWAY □ DENMARK II □ SLAVONIC □ RUSSIA □ Portuguese □ Canadian French □ Nordic □ Turkish □ Greek □ West European Latin	
Interface	RS-232(serial) / USB	
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5~24 VDC
Safety	EMC standards	FCC, CE
	Safety standards	

