VFD220D Customer Display

* Supports 11 command modes included EPSON etc.

* Power supply from 5V to 24V to prevent any mindless use of improper power input.

* 20-column x 2-line dot matrix in a wide viewing angle.

* Easy connectivity to a wide range of POS products.

* OPOS/JPOS driver is standard.

Specification

General	Display Method	Vacuum Fluorescent Display (Blue-green)
	Number of characters	40(20 columns x 2 lines)
	Brightness	500~1000 cd/m2
	Character font	5 x 7 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	**5.25 (W) x9.02 (H)mm**
	Dot Size (X x Y)	**0.86 x 1.05mm**
	Download characters	9 characters
	Panel Dimension	**220(W) x 45(D) x 125(H)mm**
	Pole Dimension	Per support length: 140(L) x 34.5(Dia)mm
	Base Dimension	205(W) x 106(D) x 33(H)mm
	Viewing Angle	Max. 90°
	Horizontal Rotation	Max. 355°
	Weight	Approx. 980 grams
Commands Mode		LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support		FRANCE□GERMANY□U.K□DENMARKI□SWEDEN□ITALY□SPAIN□JAPAN□NORWAY□DENMARKII□SLAVONIC□RUSSIA□Portuguese□Canadian French□Nordic□Turkish□Greek□West European Latin
Interface		RS-232(serial) / USB
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5~24 VDC
Safety	EMC standards Safety standards	FCC, CE

*VFD DISPLAY PD220 *
**HAVE A NICE DAY AN