15.6 Inch All In One Touch POS Terminal

(M/N:POS-L156)

OCOM POS-L156 series pos integrated high speed thermal printer inside, stylish desigin, working stablely and reliably, rich IO interface make a lot of connectivities available, easily maintain and flexibly be upgraded by customers. it is the best choice for many application sites such as retaurants, coffee shops, retail stores etc...

Features:

- l. Intel Celeron series and intel core I3 I5 processor for option
- $m. \ \mbox{Hard}$ Driver Msata SSD 64GB ,SSD 128GB and 256 GB for option
- n. 58mm and 80mm high speed thermal printer built in for option
- o. Multi-point projected capacitive touch panel
- p. Optional side MSR and VFD220 customer display mounted to back cover
- q. Ture flat and water-proof scratch-resistant surface display

Specification

ModelPOS-L156Name15.6 inch all in one touch screen point		
Name 15.6 inch all in one touch screen pe		
	os terminal	
Housing plastic with metal combined		
Color whole white machine body or whol	le black machine body	
Display		
Main screen 15.6 inch touch screen monitor		
Resolution 1366*768		
Brightness 2		
250cd/m		
View angle Horizon: 160; Vertical :150		
Touch screen Multi-point projected G+G capaciti	ve touch	
Sub-display 15.6inch display W/ or W/o to	uch function, resolution	
1366*768 for option		
Customer display 2*20 VFD mounted to back cover f	or option	
Performance		
Motherboard Intel Celeron Bay Trail J1900 2	2.0GHz ,or intel celeron	
J4125,or intel core I3 / I5 CPU for o	ption	
System Memory 1*SO-DIMM DD	RIII slot,	
support 4GB DDR3L/1333MHZ(defa	ault) ,8GB for option	
Storage device Msata SSD 64GB or higer, up to 25	6GB	
Audio On board Real Tek ALC662 audio c	On board Real Tek ALC662 audio chip	
LAN 10/100Mbs,Realtek RTL8111F Lan	10/100Mbs,Realtek RTL8111F Lan chip	
built in Mini PCI-E slot,support emb	bedded WIFI module	
Operating System Windows7/8/10, Embedded,WEPO	S,Linux	
Connectivity		

External	power button*1
I/O port J1900	12V DC in Jack*1
.,	LAN:RJ-45*1,RJ11 for cash drawer
	USB*6
	15PIN D-sub VGA *1
	RS 232*1
	line out*1,MIC in*1
Options	
80mm thermal printer	direct thermal printing
	150mm/s pringting speed
	79.5-/+ 0.5mm paper width and printable width 72mm
	with atuo cutter function and thermal head life 50km
58mm thermal printer	direct thermal printing
	85mm/s pringting speed
	57.5-/+ 0.5mm paper width and printable width 48mm
	thermal head life 50km
MSR	optional side MSR
Web camera	web camera mounted on top of the display for option
Scanner	support 1D&2D code-scanning for option
Speaker	4ohm/5w speakers inside for option
Package	
Weight	Net[]6.5Kg , Gross:8.0Kg for 15.6 with15.6 dual screen with
	printer built in
Package with foam inside	490*310*485mm
Accessories	
Power adapter	200-240V/50-60HZ(default),110-240V/50-60HZ
	AC powe rinput ,DC12/5A output adaptor for W/o printer and
	W/ 58mm printer machine
	200-240V/50-60HZ(default),110-240V/50-60HZ
	DC12V/8A out put adaptor only for W/ 80mm printer
Dewer eable	machine
Power cable	Power cable plug compatible with USA /EU / UK etc and
	customized available

















