

Windows Based 15/12 inch all-in-one Touch POS Machine with Printer (M/N:POS-C15)

Features:

- 1 Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system
- 1 2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system
- 1 2GB RAM+8GB ROM standard (Android)
- 1 2GB RAM+32GB SSD standard (Windows)
- 1 5 wire resistive touch screen(default),Capacitive screen for optional
- 1 58/80mm embedded thermal printer for optional
- 1 Magnetic member card reader for optional
- 1 VFD customer display or vice screen

Applications:

- 1 Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- 1 Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- 1 Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- 1 Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Picture show:



Parameter

Model	POS-C15	
Color	Silver-gray or Black	
CPU①	Intel Celeron J1900 Quad core 2.0 GHZ	
CPU②	2.0GHz A83T ARM 8-Core Cortex-A7 Processor	
Memory①	DDRIII 1066/1333*1 2GB (default) (Windows)	
Memory②	2GB RAM 8GB ROM □Android□	
OS①	Windows7(Beta)	
OS②	Android 5.1	
Hard Driver	SSD 32GB (default) (Windows)	
LCD panel Size	15 inch TFT LCD	
Brightness	350cd/m2	
Resolution	1024*768(max)	
Touch Screen	5 wire resistive touch screen	
Printer Parameter	Print Density	203dpi
	Printing Command	ESC/POS
	Paper Roll Diameter	60mm
	Paper Width	58mm or 80mm
	Printing Speed	60mm/s or 150mm/s
	MCBF(life)	50km
Other optinoal funtion	MSR/ VFD220 customer displaiy/ vice screen	

View Angle	Horizon: 150; Vertical :140
I/O port□J1900□	1* power button 12V DC in jack*1
	HDMI*1
	VGA(15Pin D-sub)*1
	LAN:RJ-45*1
	USB(2.0)*4
	RS232*2
	MIC IN*1 Audio out*1
I/O port□A83T□	RJ11*1 (Optional)
	TF slot *1
	RJ45*1
	HDMI for vice screen
	DB9 RS232 port*1□USB*2
	Audio*1
Operating temperature	0°C to 40°C
Storage temperature	-20°Cto 60°C
Operating System	Windows XP above, Embedded,WEPOS, Linux
Power adapter	110-240V/50-60HZ AC power, Input DC12/5A out put