

# Wireless Mini Handheld Stocktaking Terminal 2015

## Features:

Wireless Mini Handheld Stocktaking Terminal 2015

Mini data collector, convenient and portable;

Wireless working distance can meet general request, 30 to 300m in open area;

Can store 30,000 bar codes;

Instantly store and bulk transfer mode, secure to keep the data;

Auto-turn-off at low voltage. Settable standby time, high efficiency and energy saving;

Easy and comfortable operation;

## Specification:

Wireless Communications:	
Modulation	GFSK
Transmission rate	200Kbps
Power	10dBm
Transmission Distance	Visual straight line distance 300 meters
Antenna	Built-in spring antenna
Performance Characteristics	
Light Source	650nm laser
Supported barcodes	EAN-8□EAN-13□UPC-A□UPC-E□Code 39□Code 93□Code 128□EAN128□Codabar□Industool 2 of 5□Interleave 2 of 5□Matrix 2 of 5□MSI etc
Scanner Type:	Bi-directional
Scan rate	48±2 scan/second
Scan distance	10-520mm
Scan width	20mm@window□220mm@200mm
Resolution	0.10mm□pcs0.9□
Depth of Field	0□250mm□0.33mm□PCS 90%□
Working Way	Triggered or automatic (continuous mode) scanning
Physical Characteristics	
Memory:	1M (Can store 30,000 barcodes)
Interfaces:	Standard configuration mini USB receiver; RS232 and PS2 optional
Current:	96mA (working) 46mA(standby)
Battery:	Built-in rechargeable lithium ion battery (3.7V, 1900mAh)
Material	ABS+PC
Dimension:	102mmX46mmX28mm (Data Collector) 52mmX20mmX10mm (Receiver)
Weight:	130g (with battery)
User Environment	
Operation Temperature	-20 Degree C□45 Degree C
Storage Temperature	-20 Degree C□60 Degree C
Humidity:	5~95% relative humidity, non-condensing
Safe	
EMI/RFI:	CE & FCC DOC compliance
Safety Standard	The second national laser safety standards
Ordering Information	
OCBS-D004	433MHZ Wireless Mini Portable Stocktaking Terminal
OCBS-D104	USB Cable Mini Portable Stocktaking Terminal

**Product Details:**



**Relevant documents:**

Do you want to know more product information?Please Click here.

- [Specification](#)
- [OCBS-D004 USB receiver Driver](#)
- [OCBS-D004 PC Application](#)