# Handheld android mobile pos terminal with printer (POS-T8)

Features:
1.Android 4.4 operation system.
2.Adopts Qualcomm quad-core 1.2GHz processor.
3.4.0 inches IPS capacitive touch screen.
4.Safety and reliable design
5.Passed Unionpay Pboc L1 & amp; L2; passed PIN input safety certification.
6.Unionpay direct connect POS network access.
7.Support Pirnting Receipt and Barcode reading
8.Supports magnetic stripe card, IC card, contactless card.

| Specifications: | |
|---|---|
| System Parameters | |
| CPU | Qualcomm quad-core 1.2GHz |
| OS | Android 4.4 |
| RAM / ROM | ROM 4GB eMMC; RAM 512MB / 1GB DDR2; |
| | support external micro SD card, 32 GB at most |
| Display | 4.0 inch capacitive, multi touch; 480 * 800, IPS display |
| Keypad | 3 Touch System Keys, 15 physical keys (include Power key, Custom key, POS Cipher key and Command key) |
| Battery | Lithium polymer battery, 4000mAh |
| Functional Configuration | |
| Camera | Rear Camera 5M AF (support flashlight), Front Camera 0.3M wide angle |
| Printer | Built-in 2 inches thermal printer |
| Navigation | Built-in GPS, support AGPS |
| Indicator Light | System indicator light, POS indicator light |
| Audios | Built-in speaker, buzzer, microphone, vibrator |
| Sensors | Gravity sensor |
| POS | |
| Sound Wave Payment | Support |
| Magnetic Strip Card | Triple track MSR, bi-directional swiping ISO7811, 7812 |
| IC Card | 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV |
| Contactless card | 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC |
| SAM Card | 1 SAM Solt, ISO7816 |
| Cipher Keyboard | Built-in keypad |
| Network Parameters | |
| Network Type | WCDMA / GSM |
| Network Spectrum | WCDMA 2100MHz |
| | GSM / GPRS / EDGE 850/900/1800 / 1900MHz |
| WLAN | 802.11 a / b / g / n Built-in Antenna |
| Voice / Data Service | Support |
| WPAN | Bluetooth V4.0 + EDR |
| External Interface | |
| USB Interface | Micro USB2.0, support USB OTG |
| Charger Jack | DC JACK |
| Power Supply Jack | Pogo Pin, 5V - 500mA |
| Communication | USB, RS232 |

| Physical Parameters | |
|---|---|
| Dimensions | 205mm H * 82mm / 67mm W * 33mm D |
| Weight | 500g (battery included) |
| Operating Temp | -20 ° C ~ 60 ° C |
| Storage Temp | -40 ° C ~ 80 ° C |
| Humidity | 10% ~ 90% RH non-condensing |
| Drop Test | 1.0-meter drop protection |
| Roller Drop Test | 500 times |
| ESD protection | ± 8KV contact discharge; ± 15KV air discharge |
| Development Environment | |
| System Environment | Android 4.4 / SP-UI |
| Development Environment | SDK |
| Management Software | PC management suite / MDM |

# POS-T8

One-Stop POS & Auto-ID Related Products Supplier

www.ocominc.com

# POS-T8

One-Stop POS & Auto-ID Related Products Supplier

www.ocominc.com

CE FC RoHS

# POS-T8

One-Stop POS & Auto-ID Related Products Supplier

www.ocominc.com

OCOM

At your side

# POS-T8

One-Stop POS & Auto-ID Related Products Supplier

www.ocominc.com

CE FC RoHS