## handheld touch screen android 1d barcode barcode reader pda

(OCBS-D5000)

# **Product Description**

### Feature:

- Android 7.0
- 1GB RAM, 16GB ROM
- Gorilla 5.0 in. 720\*1280 Gorilla HD Screen
- Rugged IP65/1.5m Drop Tolerance
- Rechargeableli-ion polymer, 3.7V, 8000mAh Battery
- Rear Camera 8 MP, auto-focus with LED flash
- Support 4G/Wifi/GPS/Bluetooth
- HHW SoftwareDevelopment Kit
- 1D/2D BarcodeScanner(optional)
- RFIDLF/HF/UHF/NFC (optional)
- TCS1SMCapacitive Fingerprint Sensor(optional)

SPECIFICATIONS			
PHYSICAL CHARACTERISTICS			
Dimension	170mm(H)x85mm(W)x23mm(D)±2 mm		
Weight	Net Weight :380g (including battery&wrist strap)		
Display	Gorilla 5.0 in. TFT-LCD(720x1280)touch screen with backlight		
Backlight	LED backlight		
Keypads	3 TP keys, 6 function keys, 4 side buttons		
Expansions	2 PSAM, 1 SIM, 1 TF		
Battery	Rechargeable li-ion polymer, 3.7V, 8000mAh		
PERFORMANCE CHARACTERSTICS			
CPU	Quad A53 1.5GHz quad-core		
Operating System	Android 7.0		
Storage	2GB RAM, 16GB ROM, MicroSD(max 32GB expansion)		
USER ENVIRONMENT			
Operating Temp.	-20°C to 50°C		
Storage Temp.	-20°C to 70°C		
Humidity	5%RH to 95%RH(non-condensing)		
Drop Specifications	5ft./1.5 m drop to concrete across the operating temperature range		
Sealing	IP65, IEC compliance		
ESD	±15kv air discharge, ±8kv direct discharge, ±8kv indirect discharge		
DEVELOPMENT ENVIRONMENT			
SDK	HHW Software Development Kit		
Language	Java		
Environment	Android Studio or Eclipse		
DATA COMMUNICATION			
WWAN	TDD-LTE Band 38, 39, 40, FDD-LTE Band 1,2,3, 4,7;		
	WCDMA(850/1900/2100MHz);		
	GSM/GPRS/Edge 850/900/1800/1900MHz);		

WLAN	2.4G/5G Dual Frequency, IEEE 802.11 a/b/g/n/ac		
WPAN	Bluetooth Class v2.1+EDR, Bluetooth v3.0+HS, Bluetooth v4.0		
GPS	GPS(embedded A-GPS), accuracy of 5 m		
DATA CAPTUER	•	·	
BARCODE READER(OPTIONAL)			
1D barcode	1D laser engine	Honeywell N431x	
	Symbologies	All major 1D barcodes	
2D barcode	2D CMOS Imager	Honeywell N6603	
	Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode, Postal Codes, US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal. etc.	
COLOR CAMERA			
Resolution	8.0 megapixel		
Lens	Auto-focus with LED flash		
RFID READER(OPTIONAL)			
RFID LF	Frequency	125KHz/134.2KHz(FDX-B/HDX)	
	Protocol	ISO 11784&11785	
	R/W Range	2cm to 10 cm	
RFID HF	Frequency	13.56MHz	
	Protocol	ISO 14443A&15693	
	R/W Range	2cm to 8cm	
RFID UHF	Frequency	865~868MHz or 920~925MHz	
	Protocol	EPC C1 GEN2/ISO 18000-6C	
	Antenna Gain	Circular antenna(2dBi)	
	R/W Range	1 m to 1.5 m(tags and environment dependant)	
Active 2.45GHz	Read range more than 200 m (customization)		
433MHz	Read range more than 200 m (customization)		
ZigBee READER(OPTIONAL)			
Protocol	IEEE 802.15.4 (customization)		
Reading Range	100 m to 200 m(customization)		
FINGERPRINT READER(OPTIONAL)			
Sensor	TCS1SM		
Sensor type	Capacitive, area sensor		
Resolution	508 DPI		
Performance	FRR<0.008%, FAR<0.005%		
Capacity	1000		
PSAM SECURITY(OPTIONAL)			
Protocol	ISO 7816		
Baudrate	9600, 19200, 38400,43000, 56000, 57600, 115200		
Slot	2 slots(maximum)		
ACCESSORIES			
1xDC ch		n Polymer Battery arging cable ata cable	
Optional	Cradle,H	andle, UHF gain board	









#### **FAQ**

#### 1. MOQ policy

No MOQ limitation for the standard products, but the unit price is different, bigger quantity better price.

For customized production, you can discuss the MOQ with our sales representative directly.

#### 2. Sample Availability & Policy

After customers confirmed the specification, we are very glad to provide samples for testing and qualification.

All samples should be paid before shippment, the samples price is a higher than mass order. When the mass order placed, we can return you the samples cost, or send you more piece products with the shippments.

You can buy the samples from us directly using t/t, western union, or paypal. And you can also buy it on our online store.

#### 3. Warranty

OCOM is dedicated to providing most cost-effective products and services with reliable quality that will

meet customers'satisfication;

We was qualified by global fortune 500 company, and we have the top 1 level trade assurance which 100% protect your money and lead time.

Our warranty of the products is about 12+1 months from the shipment normally, some designated models can have as long as 24 months warranty;

Any product within 30 days of delivery failure occurs shall be deemed invalid delivery (DOA). DOA products will give priority to the replacement, and shipped by courier.

For mass order, we would like to supply some spare parts with shipment for local quickly repair. And after that, you can returned failure parts for rework and analysis.

#### 4. Payment Terms

For mass order, you can pay us by using T/T, LC, Western Union, Escrow or others. About samples order, T/T, Western Union, Escrow, Paypal are acceptable. Currently, you can pay using Moneybookers, Visa, MasterCard and bank transfer. You can also pay with select debit cards including Maestro, Solo, Carte Bleue, PostePay, CartaSi, 4B and Euro6000.

#### 5. Shipment

We accept all kinds of shipping ways including: express, air, sea, truck, or pick up by customers personally.

#### 6. Customer

Our main customers from Eruopean, Australia, and the fast growing South America, Africa, Russia...,

We have servered more than 2300 customers from 159 countries, including the global fortune 500 company like Unilever, O2.....50 of them are the biggest distributor in the local teritories.

#### Why You Choose OCOM?

- ·Leading One-Stop POS and Auto-ID Related Products Supplier Qualified by Global Fortune 500 Companies
- ·Tier 1 customers including Unilever, O2, Star...
- ·2300+ Customers Cover 159 Countries;
- ·11 Years OEM/ODM Experience.
- ·Top 1 Level Trade Assurance in POS industrial quarantee quality and shipment date
- ·Fast respondes and professional service
- ·ISO, FCC, CE, Soncap, POA, BIS, and other Certificates
- ·12+1 months wanrranty.
- ·Shortlisted in "China Best Employer Award"
- ·Belief: Integrity Based, Strive for Excellence, Win-win Cooperation