

Aluminum 15.6" Touch Screen All in One Touch Pos Terminal windows E Pos Retail Pos All in One for Shop Checkout

(M/N: POS-1562)

OCOM POS-1562 POS terminal has aluminium alloy shell and base, it has Intel Celeron and Android series CPU for option, it has rich I/O interfaces to be connected to more external devices.

Features:



Good heat dissipation system make POS work well in harsher environment;

Super-slim touch screen display and stylish design improve your higher profile;

More scientific separated structure for easy maintenance and disassembly.

Specification

Model	POS-1562-W	POS-1562-A
Name	15.6 inch touch POS terminal	
Housing material	Aluminium alloy housing and base	
Display		
Main screen	15.6 inch touch screen monitor	
Resolution	1366*768	
Brightness	220cd/m2	
View angle	Horizon: 90, Vertical: 60	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	11.6 inch display W/ or W/o touch function for option	
Performance		
Motherboard	Intel Celeron J6412, 2.0GHz Intel core I3 CPU for option	Rockchip series RK3568, quad core 2.0G
System memory	1*SO-DIMM DDR4 slot, support 3200mHZ, 4GB /8GB /16G for option	On board DDR4 4GB, 8G for option
Storage device	64GB M.2 SSD or higher, up to 512GB	on board 32GB EMMC 64GB for option
LAN/WLAN	10/100/1000Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot, support embedded WIFI module	10/100/1000Mbs,Realtek RTL8111F Lan chip□Support Wi-Fi 802.11a/b/g/n, BT3.0/BT4.0
Operating system	Support Windows 10/11	Android 11
Connectivity		

External I/O port J6412	Power button*1
	12V DC in jack*1
	LAN: RJ-45*1, USB*6, COM*2, HDMI*1
	Line out & MIC in 2in1 JACK *1
External I/O port RK3568	Power button*1
	12V DC in jack*1
	LAN:RJ-45*1, USB*6, COM*1
	Line out*1
Environment	
Operating temperature	0 to 50 degrees centigrade
Storage temperature	-20 to 60 degrees centigrade
Working humidity	10%~90% No condensation
Storage humidity	10%~90% No condensation
Package	
Weight	Net weight 3.6kg, gross weight 4.9kg
Package with foam inside	430*240*370mm
Accessories	
Power adapter	110-240V/50-60HZ AC power input, DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available







