

Supermarket pos touch screen all in one pc electronic cash register

(M/N: POS -E15-W/A)

Features:

Support Windows or Android OS;

Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system;

RK3288 Quad core Processor for Android system;

2GB RAM+8GB ROM standard (Android);

2GB RAM+32GB SSD standard (Windows);

15.6 inch Multi-point capacitive touch screen;

Support 15.6 or 11.6 inches non-touch second screen;

Embedded 58/80mm thermal printer(Optional);

Embedded MSR RFID reader (Optional).

Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop;

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop;

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket;

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf.

Picture show:



Parameter:

Model	POS -E15.6-W / POS -E15.6-A
Main Board1	Intel Celeron Processor J1900 Quad core 1.99GHz (Windows)
Main Board2	RK3288 Quad core Processor (Android)
OS1	Windows7 (Beta)
OS2	Android 6.0
Memory1	2GB RAM 32GB SSD (Windows)
Memory2	2GB RAM 8GB eMMC (Android)
Touch Screen	Multi-point capacitive touch
Screen Size	15.6 inch, 16:9
Resolution	1366*768
Customer Display	LCD customer display (Default), Options: 11.6 or 15.6 inches non-touch screen, VFD customer display,
Color	Black
Printer	58mm big gear thermal printer or 80mm thermal printer with Auto cutter (Options)
I/O port (1J1900)	USB*6
	RJ45*1
	RJ11*1 (optional)
	VGA*1
	HDMI*1 (for vice screen)
	DB9 RS232 port *2(can up to 4 COM port)

I/O port(2RK3288)	RJ11*1 (Optional)
	TF slot *1
	RJ45*1
	HDMI*1 (for vice screen)
	USB*2 (can add 4 ports for optional)
	DB9 RS232 port*1
	Audio*1
Operating temperature	0°C to 40°C
Other Function (Android)	Bluetooth, WIFI
Optional items (Windows)	RFID, MSR, LCD VFD i-Button, DB25 parallel port, DB9 RS232 port*4
Optional items (Android)	3G, 4G, LCD VFD display, RFID, MSR, I-Button
Storage temperature	-20°C to 60°C
Power adapter	110-240V/50-60HZ AC power Input, 12/24V output depending on the printer



POS-E15





POS-E15





POS-E15





POS-E15











2*20(VFD/LCD)



POS-E15





POS-E15





80MM thermal printer with automatic cutter



58MM large gear thermal printer



No disassembly, easy replacement

