

# wireless 80mm POS printer machine OCPP-88A-W

(Model: OCPP-88A-W)

## Features:

1. Unique appearance with reliable mold;
2. High-speed printing at speeds up to 300 mm / sec;
3. Optional automatic cutter;
4. Line and options Cordless Telecommunications
5. Provide a variety of interfaces: USB, USB + serial, USB + LAN, USB + serial + LAN; and Wifi + USB, Bluetooth + USB + LAN
6. audible alarm application support is available for the kitchen;
7. Support various types of one-dimensional and two-dimensional bar code printing;
8. Supports a variety of international languages;
9. SDK for Android provides;
10. Reliable print head life and one hundred kilometers;
11. Compatible EP SON ESC / POS command.

## Parameters:

|                      |  |
|----------------------|--|
| Printing Methods     | Thermal line printing  |
| Printed characters   | 576dots / line (default), 512dots / line;<br>Characters: Simplified Chinese point of 24x24, 18030 font support, support for Taiwan and Hong Kong, traditional (complex Font), ANK character; |
| Font                 | A: 12 * 24dots, 1.5 (W) * 3.0 (H) mm;<br>B: 9 * 17dots, 1.1 (width) * 2.1 (H) mm<br>Simplified / Traditional: 24 * 24dots, 3.0 (W) * 3.0 (H) mm  |
| Barcode types        | JUPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128, QR code  |
| Print speed          | 250 mm / sec as a single interface, to 300mm / sec Dual interface and triple interface   |
| Interface            | USB, USB + serial, USB + LAN, USB + Serial + LAN, Wireless + USB, Bluetooth + USB + LAN  |
| Print command        | Compatible with EPSON ESC / POS command  |
| Driver               | In Win9X / Window XP / Win VISTA / WIN2000 / Win2003's / Win / Win 7 8 / win8.1 / Linux is, and ESPON, SDK provides compatibility with Android.  |
| Print width          | 79.5 ± 0.5 mm (printing width 72)  |
| Paper diameter       | 83 mm  |
| Paper Thickness      | 0.06-0.08mm  |
| Knife                | Automatic cutter (optional)  |
| Print Reliability    | One hundred kilometers   |
| Power                | DC24V / 2.5A   |
| Temperature          | 0-45 degrees Celsius   |
| In contrast humidity | 10-80%   |
| Dimensions           | 190 * 145 * 145 (MM)   |
| Weight               | 1.60 kg  |

|                      |               |   |
|----------------------|---------------|---|
| Ordering Information | P / N         | Description                                       |
|                      | OCPP-88A-U    | USB ports support automatic cutter                |
|                      | OCPP-88A-UR   | USB + serial ports, supporting automatic cutter   |
|                      | OCPP-88A-UL   | USB + LAN ports support auto-cutter               |
|                      | OCPP-88A-URL  | USB + serial + LAN ports with automatic cutter    |
|                      | OCPP-88A-W    | Wireless + USB port, automatic cutter             |
|                      | OCPP-88A-BUL  | Bluetooth + USB + LAN, support automatic cutter   |
|                      | OCPP-88A-U0   | USB port, no automatic cutter                     |
|                      | OCPP-88A-UR0  | USB + serial, no automatic cutter                 |
|                      | OCPP-88A-UL0  | USB + LAN port, no automatic cutter               |
|                      | OCPP-88A-URL0 | USB + serial + Lan port, without automatic cutter |
|                      | OCPP-88A-W0   | Wireless + USB port, no automatic cutter          |
|                      | OCPP-88A-BUL0 | Bluetooth + USB + LAN, no automatic cutter        |

