

433Mhz Wireless Handheld Long Transmission Distance Laser 2d BarCode Scanner

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with <u>supplementals</u> , <u>BooklandEAN</u> , ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, <u>Trioptic Code 39</u> , Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, <u>Codabar</u> , MSI, Chinese 2 of 5, GS1 Data <u>Barvariants</u> , Korean 3 of 5, ISBT <u>Concat</u>
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, <u>Maxicode</u> , QR Code, <u>MicroQR</u> , Aztec
Interface	USB (<u>Wireless receiver cable</u>)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h