

Modelo	- T2
Nome	5,5 polegadas tela de toque capacitiva, apoiar a assinatura eletrônica
Bateria	3.8 V/ 64 00mAh
Adaptador de energia	Entrada 100-240V , 50/60Hz ,1,5A Saída 5 V CC /2 A
Interface do carregador	USB tipo C
Tela principal	Tela sensível ao toque HD de 5,5 polegadas exibição
Resolução	720*1280 IPS
Desempenho	
CPU	Processador Deca-core MT6797 Tri-Cluste-A72 * 2 A53 * 8 2,3 GHz
BATER	3 GB
Clarão	Flash de 16 GB
Comunicação	2G/3G/ 4G
Sistema operacional	Android 8,0
Botão	Botão liga / desliga, botão Digitalizar ,Botão de volume
Bluetooth	Bluetooth 4.0
WI-FI	Wi-Fi 802.11 bgnac
Impressora	Recibo Térmico de 58mm e etiqueta Impressora
Rolo de papel	Largura: 58mm; Diâmetro: ≤40mm
Scanner	5 megapixels Decodificação de câmera , Scanner 2D (opção)
NFC	Suporte ISO/IEC 14443A&B, Mifare, cartão felica
Slot SIM	Sim*2 (padrão) ou Sim*1Sam*1 para opção
Palestrante	Alto-falante de áudio digital
Dedo p rint	FBI/STQC Dedo p rint (Opcional)
GPS ou AGPS	Suporte GPSAGPS
MDM	Apoiar
Acessórios periféricos	
Acessórios	USB Tipo C*1
	Carregando adaptador * 1
	manual do usuário * 1
Ambiente	
Temperatura de operação	de 0 para 40 graus centígrados
Temperatura armazenamento	de - 10 para 60 graus centígrados
Umidade de trabalho	10%~80%
Umidade armazenamento	de 10%~90%

POS Terminal with Thermal Label and Receipt Printer

Model: POS-T2



»» Features:

- 5.5-inch Handheld Android POS Terminal
- Deca-core MT6797 Tri-Cluste-A72*2+A53*8 2.3GHz processor
- Built-in high speed 58mm thermal receipt and label printer
- Standard 3GB RAM+16G ROM
- Built-in large volume speaker
- Built-in NFC Module
- 2*SIM card slot
- Support USB type-C fast charging
- Removable 6400mAh large capacity battery
- 1D&2D Bar code reader and fingerprint for option

»» Productl Details:



»» Productl Specification:

General	
Model	POS-T2
Name	5.5 inch capacitive touch screen, support the electronic signature
Battery	3.8 V/6400mAh
Power adapter	Input: 100-240V, 50/60Hz, 1.5A Output: 5V DC /2A
Charger interface	USB type C
Display	
Main screen	5.5 inch HD touch screen dispaly
Resolution	720*1280 IPS
Performance	
CPU	Deca-core MT6797 Tri-Cluste-A72*2+A53*8 2.3GHz processor
RAM	3GB
Flash	16GB Flash
Communication	2G/3G/4G
Operating system	Android 8.0
Button	Power button, Scan Button, Volume button
Bluetooth	Bluetooth 4.0
WIFI	WIFI 802.11 b.g.n.ac
Printer	58mm Thermal Receipt and label Printer
Paper roll	Width: 58mm; Diameter: ≤40mm
Scanner	5 Mega-pixel Camera decoding, 2D Scanner (optional)
NFC	Support ISO/IEC 14443A&B, Mifare, felica card
SIM slot	Sim*2 (default) or Sim*1+Sam*1 for option
Speaker	Digital Audio speaker
Fingerprint	FBI/STQC Fingerprint (optional)
GPS or AGPS	Support GPS+AGPS
MDM	Support
Peripheral accessories	
Accessories	USB type C*1 Charging adapter*1 User manual*1
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80%
Storage humidity	10%~90%