

**100scans / sec USB automaticamente barcode scanner a laser de varredura
(Modelo: OCBs-LA06)**

Especificações do produto:

Características	
Fonte:	laser visível (650-670nm)
Velocidade de digitalização:	100 scans por segundo
distância de leitura	2.5 ~ 600 mm (100% UPC / EAN)
Tipo de digitalização:	bidirecional
Resolução:	0,10 mm (4mil) no PCS 0,9
Contraste de impressão Baixa:	20%, a diferença mínima de reflexão (@ 650nm em)
capacidades de decodificação:	UPC / EAN, UPC / EAN com Suplementos, UCC / EAN128, Código 39, Código 39 ASCII completo, código 39 trioptic, código 128, código 128 ASCII completo, codabar, intercalado 2 de 5, discreto 2 de 5, Código 93, MSI , código 11, ATA, variantes de RSS, chineses 2 de 5 ...
Características físicas	
Interfaces suportadas:	PS2, RS232, USB
Voltagem:	DC + 5V +/- 5%
Trabalho atual:	100 mA
Sem carga atual:	& Amp; It; 40 □□
Fonte de energia:	poder hospedar ou energia externa (RS232)
ângulo de varredura	ângulo de elevação de 45 ° a 60 °
dimensões:	ponto L165.42mm xH89.67mm ponto xW69.72mm
Peso:	140 g (excluindo o suporte de montagem)
Suporte	Fornecido com
Cor:	Marfim ou preto
Ambiente de usuário	
Temperatura de trabalho:	0-50 degree cC
Temperatura de armazenamento:	-40 ~ 70degreeç
Umidade:	5 ~ 95% de umidade relativa, sem condensação
Descarga Eletrostática:	Confirmar a ± 15kV de descarga de ar e + 8 KV de descarga de contato
Especificações de queda de resistência:	Betão pode suportar múltiplos ensaios de queda de 1,5 m
Segurança:	
EMI / RFI:	FCC A e Classe CE
Segurança do laser:	CDRH produtos 2 a laser

Detalhes do produto:



Handheld Laser Barcode Scanner

OCBS-LA06



Product Picture





Features

Simple but not easy

Auto-Induction built in, green design



High scan rate and long reading



distance



Excellent decode capability



KBW, RS232 and USB supported

Durable construction combined with
future-proofing



All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	

Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0°C~50°C
Storage Temperature:	-40°C~70°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.

