Baixa apoio aos preços de código de barras impressora de etiquetas com fita

(Modelo: OCBP-002)

Características:

- 1. Dois métodos de impressão disponíveis: Transferência Térmica com fita e térmica direta;
- 2.Label posição automática de papel;
- 3. Labels descascar, rasgar-se automaticamente;
- 4. Compatible com abundância de software da etiqueta;
- 5.BMP, imagens PCX baixar loja;

Paralelo 6.Support e USB juntos;

- 7. Support PDF417, QR CODE, dotmatrix;
- 8. Suit para rolos de papel térmico ou etiquetas auto-adesivas;

Especificações:

Impressora	OCBP-002		
Modelo	OCDF-002		
Resolução	203 DPI (8 pontos / mm)		
Impressão Método	o Direto Transferência térmica / Thermal		
CPU	32 BOCADO		
	Tipo: Gap rótulo e marca sensoriamento preto Detecção: comprimento da etiqueta ou a detecção automática de configuração de comando do programa		
Impressão Velocidade	50,8 milímetros -101,6 mm / Sec		
Impressão Comprimento	1.727 milímetros		
Impressão Largura	25 mm ~ 104 mm		
Mídia	Papel Rolar diâmetro externo: Diâmetro máximo 105 milímetros Papel Rolo Axis: 26 mm Papel Largura: 25 mm ~ 110 mm Papel Espessura: 0,06 mm ~ 0,3 mm Mídia Tipo: gap etiqueta, Back marca, Contínuo		
Fita	Tipos: Rolo Outward Externo Diâmetro: 64 milímetros (Max) Comprimento 300M Largura: 30 mm ~ 110 mm Testemunho Inner Diâmetro: 25,4 milímetros (1 polegada) Material: Geral Wax Type, Wax / Resin tipo misto, o tipo de resina		
Memória	2MB Flash Rom, 2MB DRAM		
Imagem	Monocromático PCX, BMP (apoio após o controle de software: ICOWMFJPGEMF Imagem, pode controlar a amplificação imagem, redução, rotação, espelhamento e realçar		
Code39, Code93, Code128 (subconjunto A, B, C), UPC A / E (adicionar 2 amp; 5), Intercalado 2 de 5, EAN 8/13 (adicionar 2 & amp; 5), código de China Código Postal, industrial 2 de 5, Matrix 2 de 5, PDF417 e codificadados da matriz, (Código QR Disponível), Dados Matriz			
Interface	Paralelo Porta USB +		

Transmissão Cenário	Baud Taxa 9600, XON / XOFF, RTS / CTS		
Ao controle painel	LED * 2: Pronto, Estado Função * Chave 1: Alimentos		
Poder	CA 18V, 4000mA		
Ambiente	Operating Temperatura: 40 graus F a 104 graus F (5 graus C a 40 graus C) Armazenamento Temperatura: -40 graus F a 122 graus F (-20 graus C a 50 graus C) Operating Umidade: 30% ~ 85%, sem condensação, de ar livre Armazenamento Umidade: 10% ~ 90%, sem condensação, de ar livre		
Físico Dimensão Tamanho: L286mm * H176mm * W233mm Peso: 2.43KG (líquida)			











Features

Simple but not easy

Two printing methods availbale: Thermal Transfer with ribbon and Direct Thermal;







Compatible with plenty of label software; BMP, PCX images download store;

Support Parallel and USB together;





Suit for thermal paper rolls or self-adhesive labels;

.minc.com

All-round show





Application Area











Airline service

Clothes Store





Logistic freight

...

Bakery Shop





Parameter

Printer Model	OCBP-002	37.000
Resolution	203 DPI (8 dot/mm)	Marie
Printing Method	Direct Thermal / Thermal Transfer	
COLL	DA OFF	

LPU	DZ BIT		
Sensor	Type: Label gap and black mark sensing		
3011301	Detection: label length auto sensing or program command setting		
Printing Speed	50.8 mm -101.6 mm / Sec		
Printing Length	1727 mm		
Printing Width	25 mm ~ 104 mm		
Media	Paper Roll External Diameter: Maximum Diameter 105 mm Paper Roll Axis: 26 mm Paper Width: 25 mm ~ 110 mm Paper Thickness: 0.06 mm ~ 0.3 mm Media Type: Label gap, Back mark, Continuous		
Ribbon	Types: Outward Roll External Diameter: 64mm (Max) Length 300M Width: 30 mm ~ 110 mm Core Inner Diameter: 25.4mm (1inch) Material: General Wax Type, Wax/Resin Mixed Type, Resin Type		
Memory	2MB Flash Rom, 2MB DRAM		
lmage	Monochrome PCX, BMP (support after the software control: ICOWMFJPGEMF Picture, can control the picture amplification, reduced, rotation, mirror image and highlight		
Bar Code	Code39, Code93, Code128 (subset A, B, C), UPC A/E (add on 2 & 5), Interleaved 2 of 5, EAN 8/13 (add on 2 & 5), Code bar, China Postal Code, Industrial 2 of 5, Matrix 2 of 5, PDF417 and Data matrix Code, (QR Code Available), Data Matrix		
Interface	Parallel Port+ USB		
Transmission Setting	Baud Rate 9600, XON/XOFF, RTS/CTS		
Control panel	LED*2: Ready, Status Function Key*1: Feed		
Power	AC 18V, 4000mA		
Environment	Operating Temperature: 40°F to 104°F (5°C to 40°C) Storage Temperature: -40°F to 122°F (-20°C to 50°C) Operating Humidity: 30% ~ 85%, non-condensing, Free air Storage Humidity: 10% ~ 90%, non-condensing, Free air		
Physical Dimension	Size: I 286mm * H176mm *W233mm		

Production Line





Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
< 00°0	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
1	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
1	Barcode Scanner	40,000 Sets / Month	20,000 Sets
V	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfication.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6 JACA
V 000	Withstand Voltage Tester	CC2670A	1 0000
1	Oscilloscope	TBS1102	M. M. B. V.
V	DC Power Supply	PS-305DM	6
V	Digital Torque Meter	HP100	1
V	Calliper	GUANGLU	2
V	Multi-meter	VC890D	7
V	Test Computer	No Information	13

Certifications



Packing and Shipment





Payment





















Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Flexible Cooperation

Company Profile

This Assessed Supplier Has Been Independently Verified

Build Your Growth On Trust













OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,

Shenzhen 518054, China;

Websites: http://www.possolution.com.cn; http://www.ocominc.com;

E-mail: ocom@ocominc.com, ocomtech@gmail.com;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637,190852203; Tel/Fax: +86.755.8605.3207.

