# Leitor de código de barras a laser portátil Sense Auto 1D com suporte

# (Modelo: OCBS -LA06)

Especificação:

| | |
|---|---|
| **Características de desempenho** | |
| Fonte de luz: | Laser visível (650-670nm) |
| Taxa de varredura: | 100 varreduras por segundo |
| Distância de leitura | 2,5 ~ 600 mm (100% UPC / EAN) |
| Tipo de Scanner: | Bidirecional |
| Resolução: | 0,10 mm (4mil) no PCS 0,9 |
| Mínimo do contraste de impressão: | 20%, diferença reflexiva mínima (@ 650nm) |
| Capacidade de decodificação: | UPC / EAN, UPC / EAN com suplementares, UCC / EAN128, código 39, código 39 completo ASCII, código 39 trióptico, código 128, código 128 ASCII completo, codabar, intercalado 2 de 5, discreto 2 de 5, código 93, MSI código 11, ATA, variantes RSS, chinês 2 de 5... |
| **Características físicas** | |
| Interfaces suportadas: | PS2, RS232, USB |
| Voltagem: | DC + 5V +/- 5% |
| Atual: | 100 mA |
| Corrente ociosa: | & lt; 40 mA |
| Fonte de energia: | Alimentação de host ou fonte de alimentação externa (RS232) |
| Ângulo de Digitalização | Inclinação 45 ° Elevação 60 ° |
| Dimensões: | L165.42mm X W69.72mm X H89.67mm |
| Peso: | 140g (sem suporte) |
| Ficar de pé | Com |
| Cor: | Marfim e preto |
| **Ambiente do usuário** | |
| Temperatura de operação: | 0degree C ~ 50degree C |
| Temperatura de armazenamento: | -40degree C ~ 70degree C |
| Umidade: | 5 ~ 95% de umidade relativa, sem condensação |
| Descarga Eletrostática: | Confirme para +/- 15KV de descarga de ar e +/- 8KV de descarga de contato |
| Especificações da gota: | Suporta múltiplas quedas de 1,5 m no concreto |
| **Seguro:** | |
| EMI / RFI: | Classe A da FCC e CE |
| Segurança do laser: | Produto laser de classe 2 CDRH |

## Detalhes do produto:

## Product Picture

## Features

Simple but not easy
Auto-Induction built in, green design
High scan rate and long reading

distance
Excellent decode capability
KBW, RS232 and USB supported

## All-round show

## Parameter

| Performance Characteristics | |
|---|---|
| Light Source: | Visible laser (650-670nm) |
| Scan Rate: | 100 scans per second |
| Reading Distance | 2.5 ~600mm (100% UPC/EAN) |
| Scanner Type: | Bi-directional |
| Resolution: | 0.10mm (4mil) at PCS 0.9 |
| Print Contrast Minimum: | 20%, minimum reflective difference (@650nm) |
| Decode Capability: | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5,discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| **Physical Characteristics** | |

| | |
|---|---|
| Interfaces Supported: | PS2, RS232, USB |
| Voltage: | DC+5V+/-5% |
| Current: | 100 mA |
| Idle Current: | <40 mA |
| Power Source: | Host power or external (RS232) power supply |
| Scanning Angle | Inclination 45° Elevation 60° |
| Dimensions: | L165.42mm X W69.72mm X H89.67mm |
| Weight: | 140g (without stand) |
| Stand | With |
| Color: | Ivory and black |
| **User Environment** | |
| Operating Temperature: | 0℃~50℃ |
| Storage Temperature: | -40℃~ 70℃ |
| Humidity: | 5~95% relative humidity, non-condensing |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete |
| **Safe:** | |
| EMI/RFI: | FCC Class A and CE |
| Laser Safety: | CDRH class 2 laser product |

## Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

www.ocominc.com

# Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

Monica Fu

# OCOM Technologies Limited

**Add**: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China
**Tel**: 0086.755.8605.3207 ext 801
**Fax**: 0086.755.8605.3207 ext 868
**Web**: www.ocominc.com
**E-mail**: sales01@ocominc.com, sales01@ocomtech.com.cn
**Skype**: ocomsales01; **MSN**: ocomsales01@hotmail.com
**Ali TM**: cn1001868228; **QQ**: 1483705401
**Mobile/Wechat/Whatsapp**: 0086.189 4871 3992

Reliable One-Stop Supplier for POS and Auto-ID Related Products