

Supermercado 360 graus desktop usb windows android robusto 1d
2d scanner de código de barras omnidirecional

(S/N:OCBS-T215)

Características:



Grande janela de leitura;

Identifique rapidamente o código 1D/2D da tela;

Tomada de cabo de dados anti-pull oculto.

Especificação

Em geral	
Modelo	OCBS-T215
Interface	USB
Tensão operacional	5V
Corrente inicial	420mA
Trabalho atual	400mA
Corrente em espera	270mA
atuação	
Sensor	Exposição geral 640*480 sensor CMOS
Fonte de luz	LED vermelho
Visualização de campo	57,2°(H), 44,2°(V)
Tolerância de movimento	> 0,3 m/s
Ângulo de varredura	Inclinação ±70° @ 0° Roll e 0° Skew Role 360° @ 0° Pitch e 0° Skew Inclinação ±70° @ 0° Rolagem e 0° Pitch
Contraste do símbolo	20% de diferença refletiva mínima
Imunidade à luz ambiente	0-100.000 Lux
Profundidade de campo típica	Código 39(5mil):20mm-80mm, EAN13(13mil):10mm-160mm QR(15mil):10mm-140mm Matriz de dados (15mil):10mm-100mm PDF417 (10mil):10mm-120mm
Capacidade de decodificação	(Codabar), (Código 39), (Código 32), (Industrial 2 de 5), (Intercalado 2 de 5), (Padrão 2 de 5), (Matriz 2 de 5), (Código 93), (Código 11),(Código 128),(UPC-A),(UPC-E),(EAN/JAN-8),(EAN/JAN-13),(GS1 DataBar(RSS14) (PDF417), (Código QR), (Micro QR), (Matriz de Dados), (Aztec), (Código Hanxi)
Física	
Peso	Bruto: 640g
Pacote	230*170*95mm
Meio Ambiente	
Temperatura de trabalho e umidade	0 a 45 graus centígrados, 10% ~ 80% Sem condensação
Temperatura e umidade de armazenamento	-20 a 60 graus centígrados, 10% ~ 90% Sem condensação















Model: OCBS-T215

Interface: USB



OCBST2152214100001

Made in China





1. Introduction	1
2. Safety Precautions	2
3. Specifications	3
4. Installation	4
5. Operation	5
6. Troubleshooting	6
7. Appendix	7

HOW TO USE THE POWER SUPPLY



1. Introduction

This power supply is designed to provide a stable and reliable power source for your equipment. It is designed to be used in conjunction with the power supply unit (PSU) and the power supply unit (PSU).

2. Safety Precautions

Read the safety and other information on the shipping container before the use of the product. When handling electrical or electronic equipment, use the following safety and other precautions:

Do not touch the power supply unit or any other parts of the product when it is powered on. Do not touch the power supply unit or any other parts of the product when it is powered on. Do not touch the power supply unit or any other parts of the product when it is powered on.

3. Specifications

Rated Power: 100W
Input Voltage: 100-240V AC
Output Voltage: 5V DC
Output Current: 20A

4. Installation

Connect the power supply unit to the power source. Connect the power supply unit to the power source. Connect the power supply unit to the power source.

5. Operation

Turn on the power supply unit. Turn on the power supply unit. Turn on the power supply unit.

6. Troubleshooting

Check the power supply unit. Check the power supply unit. Check the power supply unit.

7. Appendix

Appendix A: Power supply unit. Appendix A: Power supply unit. Appendix A: Power supply unit.

© 2010 OCOM Technology Inc. All rights reserved. This document is the property of OCOM Technology Inc. and is intended for use only with the power supply unit. No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, without the prior written permission of OCOM Technology Inc.





2D Barcode Scanner
Model: OCBS-T215 Color: Black
Interface: USB
Power Input: 5V1A CE FC

OCBS T2152214100001
Made in China