

**Mini Scanner portátil Bluetooth Barcode 1D
(Modelo: OCBs-W106)**

Especificação:

| | | |
|----------------------|---|----------------|
| Equipamento | | |
| 2D CMOS | | |
| Sensor | CMOS 640x 480 | |
| Simbologias | A maioria dos 1Ds e PDF 417, código QR, de dados Matrix, código Maxi, Aztec, etc. | |
| Reading Distância | UPC / EAN / 13 mils | 30-205 mm |
| | Código 39/20 mils | 30-305 mm |
| | PDF 417/10 mils | 50 mm a 155 mm |
| | Dados da matriz / 15 mils | 52 mm a 155 mm |
| 1D LASER | | |
| Fonte de Luz | Diodo laser visível, 650nm de comprimento de onda | |
| Scanner Taxa | 200 scans por segundo (SPS) | |
| Resolução | 0,1 mm (4mil) no PCS 0,9 | |
| Leitura Distância | 1 a 80 centímetros (dependentes da resolução) | |
| Tilt Angle | 45 Degree | |
| Ângulo de inclinação | 65 Grau | |
| PCS | 0,3 | |
| Poder | | |
| Tensão Exigência | DC + 5V 5% | |
| Pico Atual | 98mA | |
| Atual ocioso | 63mA | |
| Ambiente | | |
| Temperatura | Operação: -10 graus C -50 graus C Armazenamento: -20 graus C-60 graus C | |
| Umidade | Operação: 5% -95% (sem condensação) Armazenamento: 5% -95% (sem condensação) | |
| Choque | Queda de 2,5 m sobre a superfície de concreto | |
| EMI Geração | FCC | |
| Segurança | Classe CDRH 1 produto a laser | |
| Luz Ambiente | Máx: 10, 000 lux (FL) | |
| Físico | | |
| Tamanho | 123mmx54mmx29mm | |
| Peso | 216g (com cabo) | |
| Comprimento do Cabo | 1.8m | |
| Bluetooth | | |
| Comm Dist | 10m / 100m | |
| Comunicação | Built-in SPP e HID | |
| Modo | Mestre ou Escravo | |
| Atual Consumo | 1 88mA | |
| Inativo Atual | 93mA | |
| Bateria | Li-ion 950mAH | |
| Trabalho Horas | & Gt; 10 hrs | |
| Memória | Memória 4M | |
| Como encomendar | | |
| OCBs-W106 | Mini Scanner portátil Bluetooth Barcode 1D | |
| OCBs-W206 | Mini Scanner portátil Bluetooth 2D Barcode | |

Detalhes do produto:



*Mini Bluetooth
1D/2D Barcode Scanner
OCBS-W106/W206*



Product Picture



Features

Simple but not easy

1D - Laser 650nm,
2D - CMOS 300K million pixels;



Mini size, as small as 123*54mm, 110 grams without cable;
Durable Construction: 2.5m Shock resistant;
Bluetooth Communication: Class I/II (10m/100m);



Impressive Scan Rate:
1D - about 200SPS,
2D - 600MHz Processor;



Built-in SPP and HID;
512MB memory;
Master/Slave Switchable;
900mAH Li-ion Battery;

Recharged by USB cable
or cradle (optional);



||| All-round show





Parameter

| Hardware | | |
|---------------------|--|--------------|
| 2D CMOS | | |
| Sensor | CMOS 640x 480 | |
| Symbologies | Most 1Ds and PDF 417, QR Code, Data Matrix, Maxi code, Aztec, etc. | |
| Reading Distance | UPC/ EAN /13 mils | 30 to 205 mm |
| | Code 39/ 20 mils | 30 to 305 mm |
| | PDF 417 /10 mils | 50 to 155 mm |
| | Data matrix /15 mils | 52 to 155 mm |
| 1D LASER | | |
| Light Source | Visible laser diode, wavelength 650nm | |
| Scanner Rate | 200 scans per seconds(SPS) | |
| Resolution | 0.1mm(4mil) at PCS 0.9 | |
| Reading Distance | 1 to 80cm(resolution dependent) | |
| Tilt Angle | 45 Degree | |
| Skew Angle | 65 Degree | |
| PCS | 0.3 | |
| Power | | |
| Voltage Requirement | DC+5V 5% | |

| | |
|-----------------------------|---|
| Peak Current | 98mA |
| Idle Current | 63mA |
| Environment | |
| Temperature | Operation:-10 Degree C -50 Degree C Storage:-20 Degree C-60 Degree C |
| Humidity | Operation:5%-95%(non-condensing) Storage:5%-95%(non-condensing) |
| Shock | 2.5m drop on concrete surface |
| EMI Generation | FCC |
| Safety | CDRH class 1 laser product |
| Ambient Light | Max.10 ,000 Lux(FL) |
| Physical | |
| Size | 123mmx54mmx29mm |
| Weight | 216g(with cable) |
| Cable Length | 1.8m |
| Bluetooth | |
| Comm Dist | 10m/100m |
| Communication | Built-in SPP and HID |
| Mode | Master or Slave |
| Current Consumption | 1 88mA |
| Idle Current | 93mA |
| Battery | Li-ion 950mAH |
| Working Hours | >10 hrs |
| Memory | 4M memory |
| Ordering Information | |
| OCBS-W106 | Mini Portable Bluetooth 1D Barcode Scanner |
| OCBS-W206 | Mini Portable Bluetooth 2D Barcode Scanner |

Related Parts:

1D Engine



2D Engine



| | |
|-----------------|--------------|
| Dimensions | 42x45x17mm |
| Working Current | 42mA @ 5V |
| Infrared Sensor | Auto trigger |
| Output Signal | TTL |

| | |
|-------------------|-------------|
| Dimensions | 28x14x8mm |
| Power consumption | 42mA @ 3.3V |
| Output Signal | TTL |

Production Line



Capacity

Model

Product Name

Production Line Capacity

Actual Units Produced/Orders Month

Capacity

| verified | product name | production line capacity | actual units produced(previous year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| ✓ | Thermal Printer | 40,000 Sets / Month | 250,000 Sets |
| ✓ | Dot Matrix Printer | 15,000 Sets / Month | 10,000 Sets |
| ✓ | Bluetooth Printer | 30,000 Sets / Month | 20,000 Sets |
| ✓ | Barcode Scanner | 40,000 Sets / Month | 20,000 Sets |
| ✓ | POS Machine | 5,000 Sets / Month | 10,000 Sets |
| ✓ | Magnetic Card Reader and Writer | 45,000 Sets / Month | 50,000 Sets |

✓ Indicates information has been verified onsite by TUV on 2013.7.15

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

| Verified | Machine Name | Brand & Model No. | Quantity |
|----------|---------------|-------------------|----------|
| ✓ | Ageing Tester | No Information | 6 |
| ✓ | | | |


| | | | |
|---|--------------------------|----------------|----|
| ✓ | Withstand voltage tester | UC20/UA | 1 |
| ✓ | Oscilloscope | TBS1102 | 1 |
| ✓ | DC Power Supply | PS-305DM | 6 |
| ✓ | Digital Torque Meter | HP100 | 1 |
| ✓ | Calliper | GUANGLU | 2 |
| ✓ | Multi-meter | VC890D | 7 |
| ✓ | Test Computer | No information | 13 |

✓ Indicates information has been verified onsite by TUV on 2013.7.15

Certifications



Packing and Shipment



Double wall corrugated board



Double outer cartons

Marks and fragile stickers



Outer protective film



Payment



Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

This Assessed Supplier Has Been
Independently Verified

Build Your Growth On Trust



TÜVRheinland®
Precisely Right.



OCOM Technologies Limited, founded in 2007, is one of the leading suppliers of POS and Auto-ID related products from China.

OCOM's product portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and are hot-selling in Europe, Australia, Asia, and other areas.

OCOM has a professional team including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years. All of the sales have more than 5 years' experience, which helps us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like to establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

 Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;

Websites: <http://www.thermalprinter.com.cn> ; <http://www.ocominc.com> ;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



Documentos relevantes:

Você quer saber mais produtos informação?Por favor Clique aqui. 

[Especificação](#)