Alta qualidade 433Mhz ou Bluetooth Wireless Código QR 2D Barcode Scanner Com Cradle

Modelo: OCBS-W231-4 / B

Características:
1, 433Mhz Distância de comunicação sem fio ao ar livre 300m, indoor 100m; Bluetooth comunicação sem fio distância ao ar livre 20m, e 10m interior;
2, equipado com a comunicação ea base de carregamento
3, tampa plástica macia para proteger a lente eo esboço realça extremamente o desempenho do anti-gota;
4, o código de barras na tela dos computadores e dos telefones móveis "pode ser feito a varredura;
5, nenhum excitador da necessidade, plugue e jogo;
6, pode armazenar mais de 10.000 partes de dados;
7, vários scanners podem ser conectados a um receptor (433mhz).

Parâmetros:

Apontando Fonte de Luz	617 nm LED
Fonte de Luz de Iluminação	LED de 625 nm
Ângulo de varredura	39 ° (H) x 25 ° (V)
Ângulo de rotação	0 - 360 °
Ângulo de elevação	± 65 °
Ângulo de inclinaçao	± 60 °
Contraste de impressão	Superior a 25%
1D	UPC / EAN, UPC / EAN com suplementos, BooklandEAN, ISSN, UCC Código de Extensão de Cupão, Código128, GS1-128, ISBT 128, Código 39, Código 39 ASCII Completo, Código Trióptico 39, Código 32, Código 93, Código11, Matriz 2 De 5, Entrelaçado 2 de 5, Discreto 2 de 5, Codabar, MSI, Chinês 2 de 5, GS1 Data Barvariants, Coreano 3 de 5, ISBT Concat
2D	PDF417, MicroPDF417, Códigos Compostos, TLC-39, Matriz de Dados, Maxicode, Código QR, MicroQR, Aztec
Interface	USB (cabo receptor Wirelless)
Distância de comunicação	433mhz: Dentro: 100m; Exterior: 300m (Máx.) Bluetooth: Dentro: 10m; Exterior: 20m (Max)
Temperatura de operação	-10 deg C - 45 deg C
Temperatura de armazenamento	-20 deg C - 65 deg C
Umidade de funcionamento	5% -85%
Umidade de armazenamento	5% -95%
Durabilidade	Resiste a várias gotas de 1,5m no concreto
Potência de entrada	DC 5V, 280mA
O tempo de carga	6h
Bateria	1500mAh
Lumination	Interior: 3.000 LUX max; Luz solar exterior: 86000LUX max

Grau de IP	IP42		
DECODE RANGES			
Desempenho típico *		Intervalos de trabalho típicos	
		Faixa de foco HD	
Tipo de código de barras	Densidade do símbolo	Perto	Longe
Código 39	5,0 mil	5mm	90mm
100% UPCA	13,0 mil	8mm	200mm
Código 39	20,0 mil	8mm	250mm
PDF 417	6,8 mil	5mm	95mm
Matriz de dados	10,0 mil	5mm	110mm
Código QR	20,0 mil	10mm	150mm
Resolução 1D Código 39	4 mil		
Matriz de dados de resolução 2D	10 mil		
Material	ABS + PC		
Dimensão	Scanner (70 * 95 * 168mm) Base (145 * 112 * 74mm)		
Peso líquido	Scanner 185g Base 186g		
Informações sobre pedidos:	**OCBS-W231-4:** 433mhz wireless 2d scanner de código de barras com suporte		
	OCBS-W231-B: Bluetooth 2d barocde scanner com suporte		

FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE

LONG DISTANCE WIRELESS COMMUNICATION

STRONG DECODING ABILITY

CHARGING CRADLE

STABLE STRUCTURE

NO NEED DRIVER, PLUG AND PLAY

1 FAST SCAN,HIGH RECOGNITION RATE

3 CRADLE FOR CHARGING AND WIRELESS COMMUNICATION

4 STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE

5 NO NEED DRIVER PLUG AND PLAY

The product family

Product packaging figure

WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER

PRODUCT INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Barvariants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wirelless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside:20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base(145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.