

Alta qualidade 433MHz Wireless QR Code Scanner de código de barras 2D com berço

Modelo: OCBS-W231

Características:

- 1, distância de comunicação sem fio 433MHz ao ar livre 300m, 100m interno; Distância de comunicação sem fio Bluetooth ao ar livre 20m, e 10m indoor;
- 2, equipado com a base da comunicação e de carregamento
- 3, tampa plástica macia para proteger a lente e o esboço realça extremamente o desempenho da anti-gota;
- 4, o código de barras na tela dos computadores e dos telefones móveis pode ser digitalizado;
- 5, nenhum excitador da necessidade, plugue e jogo;
- 6, pode armazenar mais de 10.000 partes de dados;
- 7, os scanners múltiplos podem ser conectados a um receptor (433MHz).

Parâmetros:

Apontando a fonte luminosa	617 nm LED
Fonte luminosa de iluminação	625 nm LED
Ângulo de digitalização	39 ° (h) x 25 ° (v)
Ângulo de rotação	0-360 °
Ângulo de elevação	± 65 °
Ângulo de inclinação	± 60 °
Contraste de impressão	Superior a 25%
1D	UPC/EAN, UPC/EAN com suplementações, BooklandEAN, ISSN, UCC cupom de código estendido, Code128, GS1-128, ISBT 128, código 39, código 39 completo ASCII, código triótico 39, código 32, código 93, Code11, Matrix 2 de 5, Interleaved 2 de 5, discreto 2 5, co, MSI, chinês 2 de 5, GS1 data Barvariants, coreano 3 de 5, ISBT Concat
2D	PDF417, MicroPDF417, códigos compostos, TLC-39, matriz de dados, MaxiCode, código QR, MicroQR, Aztec
Interface	USB (cabo receptor wireless)
Distância de comunicação	433MHz: dentro de: 100m; Fora: 300m (máximo) Bluetooth: para dentro: 10m; Fora: 20m (máximo)
Temperatura de funcionamento	-10 DEG c-45 DEG c
Temperatura de armazenamento	-20 DEG c-65 DEG c
Umidade de funcionamento	5%-85%
Umidade do armazenamento	5%-95%
Durabilidade	Suporta várias gotas de 1,5 m para betão
Potência de entrada	C.c. 5V, 280mA
Tempo de carregamento	6h

Bateria	1500mAh		
Lumination	Dentro de: 3,000 Lux Max; Luz solar exterior: 86000LUX Max		
IP grau	Ip42		
Decodificar intervalos			
Desempenho típico *	Intervalos de trabalho típicos		
	Gama de foco HD		
Tipo de código de barras	Densidade do símbolo	Perto	Longe
Código 39	5,0 mil	5mm	90mm
100% UPCA	13,0 mil	8mm	200mm
Código 39	20,0 mil	8mm	250mm
PDF 417	6,8 mil	5mm	95mm
Matriz de dados	10,0 mil	5mm	110mm
QR Code	20,0 mil	10mm	150mm
Resolução 1D código 39	4 mil		
Matriz de dados 2D de resolução	10 mil		
Material	ABS + PC		
Dimensão	Base do scanner (70 * 95 * 168mm) (145 * 112 * 74mm)		
Peso líquido	Scanner 185g base 186g		
Informações sobre pedidos:	OCBS-W231-4: 433MHz Wireless 2D scanner de código de barras com berço		
	OCBS-W231-b: Bluetooth scanner barocde 2D com berço		



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT
INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](#);

Whatsapp: +0086.189.4879.9080;

ocominc.com

ocominc