

OCBs-W800 433MHz sem fio de código de barras de mão scanner de 32 bits

ESPECIFICAÇÕES:

characterstics FÍSICAS	
Fonte de luz:	Visible Laser Diode (VLD) @ 650 nm
Dimensões do Scanner :	168 milímetros * 72 milímetros * 93 milímetros (W * D H *)
Receptor Dimensões:	130 milímetros * 45 milímetros * 129 milímetros (W * D H *)
Material:	ABS + TPR / liga de alumínio
Peso:	370g
Modo de digitalização:	Portátil; Modo de digitalização contínua.
Luz indicadora:	LED vermelho e azul
buzzer:	Campainha Volume ajustável
characterstics DESEMPENHO	
Largura de varredura de um campo:	60 milímetros @ 30 milímetros (De cara do motor) 98 milímetros @ 100 milímetros (do rosto do motor)
Profundidade de varredura de um campo:	10-450mm (Contraste 0,9 Densidade 0,25)
Velocidade de digitalização:	150 leituras / seg
Precisão de digitalização:	0.10-0.825mm
Bit Error Rate:	1.5 milhões)
Capacidade de decodificação:	UPC / EAN, UPC / EAN com Suplementos, UCC / EAN128, Code39, Código 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Intercalado 2 de 5, Discrete 2 de 5, Código 93, MSI, O código 11, variantes RSS, chinês 2 de 5, MSI / Plessey, UK / Plessey, EAN 128, código chinesa, GS1 DataBar série UCC / (RSS)
Bateria:	3.7V / 750mAh, Li-ion
Hora de carregar:	3,0 horas
Tempo de digitalização:	30 Horas
Atual:	95mA (de trabalho); 25mA (standby)
Angles:	Pitch: 60 °; Tilt: 45 °
Frequência de trabalho:	433MHz
Comunicação à distância:	200m (Abertas Places)
Interface de comunicação:	USB
Characterstics ambiente de usuário	
Temperatura:	-10degree Cto 45grau C (Em operação), -40degree Cto 60 graus C (armazenamento)
Humidade relativa:	5% -90% (sem condensação)
Gota Especificação:	Resiste a quedas repetidas de 1,5 m de superfície de concreto
Iluminação ambiente:	0 ~ 100.000 lux
Descarga electro-estática:	Em conformidade com ± descarga de ar 12KV e ± 6KV de descarga de contato
Certificado de Segurança:	CE, FCC, Classe 2, RoHS

Detalhes do produto:



Wireless Barcode Scanner

OCBS-W800



Product Picture





Features

Simple but not easy

Integrated non-volatile memory



Data transmission distance reaches 200m in open area



Integrated non-volatile memory



Intelligent battery management system, real-time check the remaining battery



32bit decoder ensuring excellent decoding ability



All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	10-450mm (Contrast 0.9 Density 0.25)
Scan Speed	150 scans/sec

Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh, Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
USER ENVIRONMENT CHARACTERISTICS	
Temperature	-10°C to 45°C (Operating), -40°C to 60°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at www.ocominc.com, Together we quest for the best.



Documentos relevantes:

Você quer saber mais produtos informação? Por favor Clique aqui.

[Especificação](#)

[Manual do usuário](#)