

cheap 80mm bluetooth and wifi receipt thermal printer

(M/N:OCPP-80F)

Feature:

- 1.300mm/sprintinghigh-speed, improve the printing efficiency
- 2.2048Ksuper input buffer,to avoid losing bills
- 3.Support1D,2D bar code printing
4. Support black markorientation and re-print
5. Support printer monitoringfunction,to avoid losing bills;
- 6.Excellent waterproof, anti - oil, anti-dust structure design
- 7.Movablebaffle design,support 80MM,58MM different width of paperroll printing.

Printer Parameters:

Item	Parameters
Printing Method	Thermal Line
Printing width	72mm
Resolution	576 Dots/Line or 512 Dots/Line 8dots/mm,203dpi
Print speed	300mm/Second
Interface	Internet 100M+USB+COM;USB+COM
Line Spacing	3.75mm Can adjust line spacing by command
Line No.	FontA-48Lines/FontB-64Lines/Simple,traditional Chinese-24 lines
Character	standard GB18030 simplified / traditional Chinese Fonts
Character Size	ANK character,Font A:1.5×3.0mm 12×24 dots FontB:1.1×2.1mm 9×17 dots Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)
Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Bar code	1D barcode:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D barcode QR CODE
Graphics printing	Supports bitmap download and print
Cutter Function	Half cut
Type	Thermal
Width	79.5±0.5mm
Diameter	≤80mm
Feed method	Easy feed(Clameshell feed)
Commands	ESC/POS

Power Adaptor	Input:AC 110V/220V,50~60Hz
	Output:DC 24V/2.5A
Cash Drawer output	DC 24V/1A
Input Buffer	2048K bytes
NV Flash	256K bytes
Weight	1.2KG
Dimension	186*145*135
Working	Temp:5~45 Centigrade,Humidity:10~80%
Storage	Temp:-10 ~ 50 Centigrade,Humidity:10~90%(Nodew)
Print Head Life	100KM(print density LE.12.5)
Cutter Life	1000,000times
Driver	Android,IOS,Linux,Win2000,Win2003,WinXP,Win7,Win8,Win8.1