OCBs-La04-Handheld com Auto Sense Laser Barcode Scanner

(M / N: OCBs-LA04)

Característica:
1.Auto-Indução construído em, design verde;
2. Alta velocidade de varredura e distância de leitura de comprimento;
capacidade de decodificar 3.Excellent;
4.KBW, RS232 e USB suportado;
construção 5.Durable combinado com futuro-impermeabilização;

ESPECIFICAÇÃO:

Características de desempenho	
Fonte de luz:	laser visível (650-670nm)
Taxa de digitalização:	100 scans por segundo
Reading Distância	2.5 ~ 600 milímetros (100% UPC / EAN)
Tipo de Scanner:	Bi-direcional
Resolução:	0,10 milímetros (4mil) na PCS 0,9
Contraste de impressão mínimo:	20%, diferença mínima reflexivo (@ 650nm)
Capacidade de decodificação:	UPC / EAN, UPC / EAN com Suplementos, UCC / EAN128, Código 39, Código 39 ASCII completo, código 39 trioptic, código 128, código 128 ASCII completo, codabar, intercalado 2 de 5, discreto 2 de 5, Código 93, MSI , código 11, ATA, variantes de RSS, chineses 2 de 5 ...
Características físicas	
Interfaces suportadas:	PS2, RS232, USB
Voltagem:	DC + 5V +/- 5%
Atual:	100 mA
Ociosa atual:	& Lt;40 mA
Fonte de energia:	poder hospedar ou (RS232) fonte de alimentação externa
Ângulo da exploração	Inclinação de 45 ° Elevação 60 °
dimensões:	L165.42mm X W69.72mm X H89.67mm
Peso:	140g (sem suporte)
Ficar de pé	Com
Cor:	Marfim e preto
Ambiente de usuário	
Temperatura de operação:	0 graus C ~50 graus C
Temperatura de armazenamento:	-40 grau C ~ 70 graus C
Umidade:	5 ~ 95% de umidade relativa, sem condensação
Descarga electro-estática:	Confirm a +/- descarga de ar de 15KV e +/- 8 KV de descarga de contato
Especificações de queda:	Suporta várias 1.5m cai para betão
Seguro:	
EMI / RFI:	FCC Classe A e CE
Segurança do laser:	Classe CDRH produto a laser 2

Product Picture

Features

Simple but not easy
Auto-Induction built in,
green design
High scan rate and long reading

distance
Excellent decode capability
KBW, RS232 and USB supported

Durable construction combined with future-proofing

All-round show

www.ocominc.com

Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5,discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5…
Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB

Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0℃~50℃
Storage Temperature:	-40℃~70℃
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union

7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.
OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.
OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.
You can find more information of us at: www.ocominc.com,
Together we quest for the best.