

2017 newest design all in one pos system with thermal printer

(M/N:POS-A15/A15-A)

Features:

Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system

2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system

2GB RAM+32GB ROM standard

Multi-point capacitive touch screen

Embedded 58mm or 80mm thermal printer

Embedded MSR, contact IC card reader, RFID reader (Optional)

Stylish display panel

Applications:

Catering: hotel, restaurant, fast-food restaurant, coffeeshop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Pictureshow:



Parameter:

| | |
|--------------|--|
| Model | POS-A15/POS-A15-A |
| Main Board① | Intel Celeron Processor J1900 Quad core 2.0GHz |
| Main Board② | 2.0GHz A83T ARM 8-Core Cortex-A7 Processor |
| OS① | Windows7(Beta) |
| OS② | Android 4.4.4 |
| Memory① | 2GB RAM 32GB SSD |
| Memory② | 2GB RAM EMMC 32GB |
| Touch Screen | Multi-point capacitive touch |
| Screen Size | Main screen 15.6 inch, Vice screen 15.6 inch |
| Color | Black or White |
| Printer | 58mm big gear thermal printer or 80mm thermal printer with Auto cutter |

| | |
|---------------------------|---|
| I/O port①J1900 | USB*4 |
| | RJ45*1 |
| | RJ11*1 |
| | HDMI*1(for vice screen) |
| | DB9 RS232 port *1 |
| I/O port(②A83T) | RJ11*1 |
| | TF slot *1 |
| | RJ45*1 |
| | HDMI*1(for vice screen) |
| | USB*2 |
| | DB9 RS232 port*1 |
| | Audio*1 |
| USB OTG port | |
| Operating temperature | 0°C to 40°C |
| Othter Function (Andriod) | Bluetooth, WIFI,GPS |
| Optional items(Windows) | I3 I5 CPU, LCD VFD display,RFID,contact IC card reader MSR cammera,3G, DB25 parallel port, DB9 RS232 port*3 |
| Optional items(Andriod) | 3G,cammera, LCD VFD display,RFID,contact IC card reader,MSR |
| Storage temperature | -20°Cto 60°C |
| Packing dimension | 46*43*51cm |
| Power adapter | 110-240V/50-60HZ AC power, Input DC12/5A out put |



POS-A15



www.ocominc.com

CE FC





