

Leitor portátil de código de barras a laser com sensor portátil

(OCBS -LA09)

Especificação:

Características de desempenho	
Fonte de luz:	650nm visível
Taxa de varredura:	200 varreduras por segundo
CPU	32 bits
Distância de leitura	2,5 ~ 600 mm (100% UPC / EAN)
Largura da Varredura	50 mm a 60 mm, 220 mm a 200 mm
Tipo de Scanner:	Bidirecional
Modo de operação	Sentido Automático
Resolução:	Série de alta resolução 3mil / 5mil de profundidade série de campo
Mínimo do contraste de impressão:	30%, diferença reflexiva mínima
Capacidade de decodificação:	UPC / EAN, UPC / EAN com Suplemento, UCC / EAN 128, Código 39, Código 39 Completo ASCII, Trioptic Código 39, Código 128, Código 128 Completo ASCII, Codabar, Intercalado 2 de 5, Discreto 2 de 5, Código 93, MSI, Code 11, variantes de RSS, chinês 2 de 5, MSI / Plessey, Reino Unido / Plessey, UCC / EAN 128, código chinês, série GS1 DataBar (RSS)
Ângulo de Digitalização	± 65 ° (inclinação); ± 60 ° (passo); ± 42 ° (guinada)
Características físicas	
Interfaces suportadas:	PS2, RS232, USB para opção
Voltagem:	5V DC ± 5%
Atual:	85 mA (operando); 100 (máximo)
Indicador	Beeper, LED
Material	ABS + PC
Ficar de pé	Com
Dimensões:	156 * 68 * 83 mm (L * W * H)
Peso:	235g
Cor:	Cinza ou preto
Ambiente do usuário	
Temperatura de operação:	0 °C ~ 45 °C
Temperatura de armazenamento:	-40 °C ~ 60 °C
Umidade:	5% -90% (sem condensação)
Descarga Eletrostática:	Em conformidade com a descarga de ar de +/- 15KV e +/- 8KV de descarga de contato
Iluminação ambiente	0 a 100.000 LUX
Especificações da gota:	Suporta múltiplas quedas de 1,5 m na superfície do concreto
Classificação laser	EN60825-1, classe 1

Detalhes do produto:





Features

Simple but not easy

200scan/sec high scan rate and long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined with future-proofing





Competitive price for 32bit model



|| All-round show





Parameter

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar

	Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)
Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	Optional
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey and black
User Environment	
Operating Temperature:	0°C~45°C
Storage Temperature:	-40°C~60°C
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, class 1

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which

3. INTERNATIONAL AIR MAIL, usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.

