

Leitor de código de barras a laser de 32 bits sem fio 433MHz com berço (Modelo: OCBS-W800)

ESPECIFICAÇÕES:

CARACTERÍSTICAS FÍSICAS	
Fonte de luz:	Diodo Laser Visível (VLD) @ 650 nm
Dimensões do Scanner :	168mm * 72mm * 93mm (W * H * D)
Dimensões do Receptor:	130mm * 45mm * 129mm (W * H * D)
Material:	ABS + TPR / liga de alumínio
Peso:	370 g
Modo de Digitalização:	Portátil; Modo de varredura contínua.
Luz indicadora:	LED vermelho e azul
Campainha:	Volume da Campainha Ajustável
CARACTERÍSTICAS DE DESEMPENHO	
Largura do campo de digitalização:	60mm @ 30mm □Da face do motor□ 98mm @ 100mm □da face do motor□
Profundidade do campo de digitalização:	10-450 mm □Contraste 0,9 Densidade 0,25□
Velocidade de Digitalização:	150 exames / seg
Precisão de digitalização:	0,10-0,825 mm
Taxa de erro de bit:	1 / (5 milhões)
Capacidade de decodificação:	UPC / EAN, UPC / EAN com Suplemento, UCC / EAN128, Código39, Código 39 Completo ASCII, Trioptic Código 39, Código 128, Código 128 Completo ASCII, Codabar, Intercalado 2 de 5, Discreto 2 de 5, Código 93, MSI, Código 11, variantes RSS, Chinês 2 de 5, MSI / Plessey, Reino Unido / Plessey, UCC / EAN 128, Código Chinês, série GS1 DataBar (RSS)
Bateria:	3,7 V / 750 mAh, Li-ion
Hora de carregar:	3,0 horas
Tempo de varredura:	30 horas
Atual:	95mA (trabalhando); 25mA (espera)
Ângulos:	Passo: 60 °; Inclinação: 45 °
Frequência de trabalho:	433 MHz
Distância de Comunicação:	200m □Open Places□
Interface de comunicação:	USB
CARACTERSTICA DO AMBIENTE DO USUÁRIO	
Temperatura:	-10 graus Cto 45grau C (Operacional), -40graus Cto 60graus C (Armazenamento)
Humidade relativa:	5% -90% (sem condensação)
Especificação da gota:	Suporta quedas repetidas de 1,5 m na superfície do concreto
Iluminação Ambiental:	0 a 100.000 LUX
Descarga Eletrostática:	Em conformidade com a descarga de ar ± 12KV e ± 6KV de descarga de contato
Certificado de segurança:	CE, FCC, Classe 2, RoHS

Detalhes do produto:



ocom
All your side

Wireless Barcode Scanner

OCBS-W800



Product Picture





Features

Simple but not easy

Integrated non-volatile memory



Data transmission distance reaches 200m in open area



Integrated non-volatile memory



Intelligent battery management system, real-time check the remaining battery



32bit decoder ensuring excellent decoding ability



All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	10-450mm (Contrast 0.9 Density 0.25)
Scan Speed	150 scans/sec

Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh, Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
USER ENVIRONMENT CHARACTERISTICS	
Temperature	-10°C to 45°C (Operating), -40°C to 60°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at www.ocominc.com, Together we quest for the best.



Documentos relevantes:

Você quer saber mais produto informação? Por favor Clique aqui.

[Especificação](#)

[Manual do usuário](#)