Scanner de código de barras a laser sem fio 24 GHz
(Modelo: OCBS -W600)

ESPECIFICAÇÃO:

CARACTERÍSTICAS FÍSICAS	
Fonte de luz:	Diodo laser visível (VLD) @ 650 nm-670nm
Dimensões do scanner:	164 mm * 67 mm * 95 mm(W * H * D)
Dimensões do receptor:	130 mm * 45 mm * 129 mm(W * H * D)
Material:	ABS + TPR / liga de alumínio
Peso:	235g
Modo de digitalização:	Portátil; Modo de digitalização bidirecional.
Luz indicadora:	LED vermelho e azul
Buzzer:	Volume da campainha ajustável
CARACTERÍSTICAS DE DESEMPENHO	
Largura do campo de digitalização:	60mm @ 30mm（Da face do motor） 98mm @ 100mm（da face do motor）
Profundidade do campo de varredura:	2,5-600mm（Contraste 0,9 Densidade 0,25）
Velocidade de digitalização:	100 varreduras / s
Precisão da digitalização:	0,10 mm（4mil） PCS0.9
Taxa de erro de bit:	1 / (5 milhões)
Capacidade de decodificação:	UPC / EAN, UPC / EAN com suplementos, UCC / EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Código 11, variantes RSS, chinês 2 de 5
Bateria:	3,7 V / 750 mAh, íon de lítio
Hora de carregar:	3,0 horas
Tempo de digitalização:	30 horas
Atual:	100mA (trabalhando); 40mA (espera)
Ângulos:	Pitch: 60 °; Inclinação: 45 °
Distância de comunicação:	30m
Freqüência de trabalho:	2.4G
Memória	16 MB
Interface de comunicação:	USB
CARACTERÍSTICAS DO AMBIENTE DO USUÁRIO	
Temperatura:	0grau C a 50grau C (Operativo), -40grau Ca 70 grau C (Armazenamento)
Humidade relativa:	5% -90% (sem condensação)
Especificação de queda:	Suporta quedas repetidas de 1,5 m na superfície de concreto
Iluminação ambiente:	0 ~ 100.000 LUX
Descarga eletrostática:	Conforme a ±Descarga de ar de 12KV e ±6KV de descarga de contato
Certificado de Segurança:	CE, FCC, Classe 2, RoHS

Detalhes do produto:

Product Picture

BATTERY PACK
FOR BAT-8019

Features

Simple but not easy
2.4 G wireless laser barcode scanner
Scan Speed:100scans/sec

Data transmission distance reaches 30m in open area;

Scan Time:30hours

All-round show

Parameter

PHYSICAL CHARACTERSTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm-670nm
Scanner Dimensions(W * H * D)	164mm * 67mm * 95mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	235g
Scanning Mode	Hand-held; bidirectional Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERSTICS	
Width of Scan Field	60mm@30mm（From engine face） 98mm@100mm（from engine face）
Depth of Scan Field	2.5-600mm（Contrast 0.9 Density 0.25）
Scan Speed	100 scans/sec
Scan Precision	0.10mm（4mil） PCS0.9
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5
Battery	3.7V/750mAh,Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	100mA (working); 40mA(standby)

Angles	Pitch:60°; Tilt: 45°
Communication Distance	30m
Memory	2.4G
Communication Interface	USB,RS232,PS2
USER ENVIRONMENT CHARACTERSTICS	
Temperature	0℃ to 50℃ (Operating), -40℃to 70℃ (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.
OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.
OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.
You can find more information of us at: www.ocominc.com,
Together we quest for the best.

Documentos relevantes:

Quer saber mais informações sobre o produto? Clique aqui.

Especificação