

Mini terminal de armazenamento sem fio para dispositivos móveis (Modelo: OCBs-D004)

Especificação:

| | |
|------------------------------|---|
| Comunicação Sem Fio: | |
| Modulação | GFSK |
| Taxa de transmissão | 200Kbps |
| Poder | 10dBm |
| Distância de transmissão | Distância em linha reta Visual 300 metros |
| Antena | Built-in antena primavera |
| Atuação Características | |
| Fonte de Luz | Laser de 650nm |
| Códigos de barras suportados | EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN128, Codaber, Industoal 2 de 5, Interleave 2 de 5, Matrix 2 de 5, MSI etc |
| Scanner Tipo: | Bi-direcional |
| Taxa de varredura | 48 ± 2 varredura / segundo |
| Distância de digitalização | 10-520mm |
| Largura da digitalização | @ Janela 20mm, 220 milímetros @ 200 milímetros |
| Resolução | 0,10 milímetros (pcs0.9) |
| Profundidade de campo | 0 ~ 250 milímetros (0,33 milímetros, PCS 90%) |
| Caminho de Trabalho | Provocado ou a digitalização automática (modo contínuo) |
| Físico Características | |
| Memória: | 1M (pode armazenar 30.000 códigos de barras) |
| Interfaces: | A configuração padrão mini receptor USB; RS232 e PS2 opcional |
| Atual: | 96mA (de trabalho) 46mA (modo de espera) |
| Bateria: | Built-in bateria de lítio recarregável (3.7V, 1900mAh) |
| Material | ABS + PC |
| Dimensão: | 102mmX46mmX28mm (Coletor de Dados) 52mmX20mmX10mm (Receptor) |
| Peso: | 130g (com bateria) |
| Usuário Ambiente | |
| Temperatura da operação | -20 Graus C ~ 45 Grau C |
| Temperatura de armazenamento | -20 Graus C ~ 60 Grau C |
| Umidade: | 5 ~ 95% humidade relativa, sem condensação |
| Seguro | |
| EMI / RFI: | CE & amp; Cumprimento FCC DOC |
| Padrão de Segurança | O segundo normas de segurança de laser nacional |
| Ordenação Informações | |
| OCBs-D004 | Balanço Terminal 433MHz sem fio mini portáteis |
| OCBs-D104 | Balanço Terminal Cabo USB Mini portátil |

Detalhes do produto:



Product Picture



Features

Simple but not easy

Mini data collector,
convenient and portable;



Wireless version:
working distance can meet general
request, 30 to 300m in open area;



Instantly store and bulk transfer mode,
secure to keep the data;
Can store 30,000 barcodes;



Auto-turn-off at low voltage.
Settable standby time,
high efficiency and energy saving;



Easy and comfortable operation;



All-round show





Application Area

Commercial: handheld mobile POS, chains / stores / counters data acquisition, shoes ordering, card management, bill management

Commonality: mobile government, mobile police, population information management, postal management, library management

Logistics: warehouse management, product traceability, picking medicine distribution, logistics and express, logistics and distribution

Industry: production process management, forestry data collection, three meter reading, fixed asset management,



Parameter

| Wireless Communications: | |
|--------------------------|--|
| Modulation | GFSK |
| Transmission rate | 200Kbps |
| Power | 10dBm |
| Transmission Distance | Visual straight line distance 300 meters |
| Antenna | Built-in spring antenna |

| Performance Characteristics | |
|-----------------------------|---|
| Light Source | 650nm laser |
| Supported barcodes | EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN128, Codaber, Industoal 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI etc |
| Scanner Type: | BI-directional |
| Scan rate | 48±2 scan/second |
| Scan distance | 10-520mm |
| Scan width | 20mm@window, 220mm@200mm |
| Resolution | 0.10mm (pcs0.9) |
| Depth of Field | 0~250mm (0.33mm, PCS 90%) |
| Working Way | Triggered or automatic (continuous mode) scanning |
| Physical Characteristics | |
| Memory: | 1M (Can store 30,000 barcodes) |
| Interfaces: | Standard configuration mini USB receiver; RS232 and PS2 optional |
| Current: | 96mA (working) 46mA(standby) |
| Battery: | Built-in rechargeable lithium ion battery (3.7V, 1900mAh) |
| Material | ABS+PC |
| Dimension: | 102mmX46mmX28mm (Data Collector) 52mmX20mmX10mm (Receiver) |
| Weight: | 130g (with battery) |
| User Environment | |
| Operation Temperature | -20 Degree C~45 Degree C |
| Storage Temperature | -20 Degree C~60 Degree C |
| Humidity: | 5~95% relative humidity, non-condensing |
| Safe | |
| EMI/RFI: | CE & FCC DOC compliance |
| Safety Standard | The second national laser safety standards |
| Ordering Information | |
| OCBS-D004 | 433MHZ Wireless Mini Portable Stocktaking Terminal |
| OCBS-D104 | USB Cable Mini Portable Stocktaking Terminal |

Production Line





Capacity

| Verified | Product Name | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| ✓ | Thermal Printer | 40,000 Sets / Month | 250,000 Sets |
| ✓ | Dot Matrix Printer | 15,000 Sets / Month | 10,000 Sets |
| ✓ | Bluetooth Printer | 30,000 Sets / Month | 20,000 Sets |
| ✓ | Barcode Scanner | 40,000 Sets / Month | 20,000 Sets |
| ✓ | POS Machine | 5,000 Sets / Month | 10,000 Sets |
| ✓ | Magnetic Card Reader and Writer | 45,000 Sets / Month | 50,000 Sets |

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

| Verified | Machine Name | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| ✓ | Ageing Tester | No Information | 6 |
| ✓ | Withstand Voltage Tester | CC2670A | 1 |
| ✓ | Oscilloscope | TBS1102 | 1 |
| ✓ | DC Power Supply | PS-305DM | 6 |
| ✓ | Digital Torque Meter | HP100 | 1 |
| ✓ | Calliper | GUANGLU | 2 |
| ✓ | Multi-meter | VC890D | 7 |
| ✓ | Test Computer | No Information | 13 |

Certifications



Packing and Shipment



Payment





Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

This Assessed Supplier Has Been
Independently Verified

Build Your Growth On Trust



TÜV Rheinland





FORTUNE 500
Precisely Right.



OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Europe, Australia, Asia, and other area.



OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,
Shenzhen 518054, China;

Websites: <http://www.possolution.com.cn> ; <http://www.ocominc.com> ;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



Documentos relevantes:

Você quer saber mais produtos informação?Por favor Clique aqui. 

[Especificação](#)

[OCBs-D004 receptor USB driver](#)

[OCBs-D004 PC Aplicação](#)