## mobile touch screen wireless Android pos terminal price with sim card gprs (P8000)

| Android 4.4 operation system.  Adopts Qualcomm quad-core 1.26Hz processor.  4.0 inches IPS capacitive touch screen. Safety and reliable design Passed Unionpay Pboc L1& L2; passed PIN input safety certification. Unionpay et connect POS network access. Support Printing Receipt and Barcode reading Supports magnetic stripe card, IC card, contactless card. |  |   |  |
|---|--|---|--|
| System Parameters   |  |   |  |
| CPU   | Qualcomm quad-core 1.2G                                | Qualcomm quad-core 1.2GHz   |  |
| os  |  | Android 4.4   |  |
| RAM/ROM   |  | ROM 512MB eMMC; RAM 512MB DDR2;   |  |
|   |  | support external micro SD card, 32 GB at most                                 |  |
| Display   |  | ouch; 480*800, IPS display  |  |
|   |  | physical keys (include Power key, Custom key, POS Cipher key and Command key) |  |
| Battery   |  | 700mAh  |  |
| Functional Configuration  | <u> </u>   |   |  |
| Camera  | Rear Camera 5M AF (suppo                               | ort flashlight), Front Camera 0.3M wide angle                                 |  |
| Printer   | Built-in 2 inches thermal p                            | rinter  |  |
| Navigation  |  |   |  |
| Indicator Light   |  | 5 indicator light   |  |
| Audios  |  | icrophone, vibrator   |  |
| Sensors   |  |   |  |
| POS   | ·  |   |  |
| Sound Wave Payment Support  |  |   |  |
| Magnetic Strip Card   | Triple track MSR, bi-directional swiping ISO7811, 7812 |   |  |
| IC Card   | 1 Solt, Support 1.8V/3V/5V, ISO7816, PBOC and EMV      |   |  |
| Contactless card  | 13.56MHz, ISO/IEC 14443 Type A/B, qPBOC                |   |  |
| SAM Card  | 1 SAM Solt, ISO7816                                    |   |  |
| Cipher Keyboard Built-in keypad   |  |   |  |
| Network Parameters  |  |   |  |
| Network Type  | WCDMA/GSM  |   |  |
| Network Spectrum WCDMA 2100MHz  |  |   |  |
|   | GSM/GPRS/EDGE 850/900/1800/1900MHz                     | /GPRS/EDGE 850/900/1800/1900MHz   |  |
| WLAN  | 802.11 a/b/g/n Built-in Antenna                        |   |  |
| Voice/Data Service  | Support  |   |  |
| WPAN  | Bluetooth V4.0 + EDR                                   |   |  |
| External Interface  |  |   |  |
| USB Interface   | Micro USB2.0, support USB OTG                          |   |  |
| Charger Jack  | DC JACK  |   |  |
| Power Supply Jack   | Pogo Pin, 5V500mA                                      |   |  |
| Communication   | USB, RS232   |   |  |
| Physical Parameters   |  |   |  |
| Dimensions  | 205mm H * 82mm/67mm W * 33mm D                         |   |  |
| Weight  | 500g (battery included)                                |   |  |
| Operating Temp  | -20°C ~ 60°C   |   |  |
| Storage Temp  | -40°C ~ 80°C   |   |  |
| Humidity  | 10%~90% RH non-condensing                              |   |  |
| Drop Test   | 1.0-meter drop protection                              |   |  |
| Roller Drop Test  | 500 times  |   |  |
| SD protection ±8KV contact discharge; ±15KV air discharge   |  |   |  |
| Development Environment   |  |   |  |
| System Environment Android 4.4/SP-UI  |  |   |  |
| Development Environment   |  |   |  |
| Management Software   | PC management suite/MDM                                |   |  |