Сканер 2d Android PDF417 штрих-кода
(Модель: OCBs-2002)

Технические характеристики:

Датчик изображения		КМОП
Разрешение		752 * 480
Источник Света		LED (630 нм ± 10 нм)
Интенсивность света		300 ЛЮКС (130 мм)
Освещение		0 ~ 100000 LUX
Символика	2D	PDF417, QR-код (модель 1/2), Data Matrix (ECC200, ECC000, 050, 080 100 140), ацтеков, Maxicode Л.П. код, и т.д.
	1D	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Кодабар, Китай пост 25, с чередованием 2 из 5, ISBN / ISSN, код 93, UCC / EAN-128, GS1 Databar, т.
Точность		≥ 3mil
Глубина поля сканирования		5 мм ~ 450 мм
Контрастность печати сигнала		≥ 25%
Roll / Pitch / перекоса		360 ° / 60 ° / 55 °
Интерфейс		RS232 / HID-KBW / UDP / USB COM- Порт Эмуляция / HID-POS / PS2-KBW / Bluetooth
Потребляемая мощность		1.65 Вт
Напряжение		5 В постоянного тока
Ток	Макс	330 мА
	Рабочая	290 мА
	Простой	200 мА
Вес		250 г
Размеры		164 * 126 * 73 мм
Управляйте температура		-5 градусов C~ +45 градусов C
Температура хранения		-40 градусов C~ +60 градусов C
Влажность		5% - 95% (без конденсата)
Программирование		Быстрый набор, Руководство по программированию, uTools Lite

Подробнее:

Product Picture

Features

CMOS image technology base

High speed and precision decoding

RS232, KBW and USB interfaces supported

www.ocominc.com

All-round show

Parameter

Image Sensor		CMOS
Resolution		752 * 480
Interface		RS232 / HID-KBW / UDP / USB COM Port Emulation / HID-POS
Symbology	2D	PDF417, QR Code(Model 1/2), Data Matrix(ECC200, ECC000, 050, 080,100,140), Aztec, Maxicode, LP Code, etc.
	1D	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, China post 25, Interleaved 2 of 5, ISBN/ISSN, Code 93, UCC/EAN-128, GS1 Databar,etc.
Precision		≥ 3mil
Light Source		LED(630 nm ± 10 nm)
Light Intensity		300 LUX (130 mm)
Depth of Scan Field		45 mm – 450 mm

Depth of Scan Field		45 mm ~ 450 mm
Print Contrast Signal		≥ 25%
Roll		360°
Pitch		45°
Yaw		45°
Illumination		0 ~ 100,000 LUX
Power Consumption		1.65 W
Voltage		DC 5 V
Current	Max	330 mA
	Working	290 mA
	Idle	200 mA
Weight		250 g
Operate Temperature		-5℃ - +45℃
Storage Temperature		-40℃ - +60℃
Humidity		5% - 95%(non-condensing)
Programming Software		Quick Set, Programming Guide, uTools Lite
Certification		FCC Part15 Class B, CE EMC Class B

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

www.ocominc.com

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

Соответствующие документы:

Хотите знать больше о продукте information?Пожалуйста Кликните сюда.

Спецификация