

80мм Мобильный Android IOS Bluetooth Pos термопринтер (Модель: ОСРР -M082)

Характеристики:

Размеры (Ш x Г x В)	98 x 103 x 45 мм
Вес	280 г
цвет	черный
Эффективная ширина печати	72 мм
Способ печати	Термальная Линия Печати
Команда печати	ESC / POS совместимый набор инструкций
Скорость печати	До 90мм / сек
разрешение	8 точек / мм (203DPI)
Печать шрифта	В 12X24 / 24x24 в
Емкость колонки	48/24 колонны
Размер персонажа	1,5 x 3,0 мм (ширина x высота) / 3,0 x 3,0 мм (ширина x высота)
Размер бумаги	Диаметр от 80,0 мм до ± 0,1 мм x 30,0
Толщина бумаги	От 0,06 до 0,08 мм
Набор символов	Буквенно-цифровой / китайский текст
Интерфейс	USB, RS-232, Bluetooth (опционально)
вспышка	256KB
Адаптер питания	9 В постоянного тока / 2A DC / 2000 мА 7,4 В; Аккумулятор может оставаться в течение 4-5 дней, когда он полон силы, он может печатать 120-150М бумаги
Заряд батареи	
Другие преимущества	Обнаружение бумаги, обнаружение питания, ручное выключение
Условия труда	Температура: -10degreeC~50degreeCВлажность: 10%~90%
Условия хранения	Температура: -20degreeC~70 degreeC

Информация о продукте:



**80mm Bluetooth
Thermal Receipt Printer
for Andriod or IOS**

OCPP-M082



Product Picture





Features

Simple but not easy

Support Windows, Android,
or iPhone OS;



Bluetooth, USB and
RS232 communication.

Battery charge indicator, easy to know rest power.



Higher print speed 90mm/sec.



100km TPH Life.





Low power consumption
and large capacity
Lithium battery.

All-round show





Application Area

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation,
Warehouse management, Delivery, Illegal Parking Ticket,
Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm

Delivery



Restaurant



Bus / Taxi Receipt



Traffic Citation





Overall Dimension (W×D×H)	98×103×45mm
Weight	280g
Color	Black
Effective print width	72mm
Print method	Thermal line printing
Print commands	ESC/P05/STAR compatible command set
Print speed	Up to 90mm/sec
Resolution	8 dots/mm(203dpi)
Print font	12x24/ 24x24
Column capacity	48 columns/24 columns
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(W x H)
Paper dimensions	80.0±0.1mm x diameter 30.0mm
Paper thickness	0.06 to 0.08mm
Character set	Alphanumeric/ Chinese Kanji ASCII Font A:12×24 Font B: 9x17 Korean code page 949
Communication Interface	USB/RS-232, Bluetooth
Flash	256KB
Power Adapter	9V DC/1.5A
Battery Power	7.4V DC/ 2000mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper
Other features	Paper detection, power detection, Manual shut down
	Temperature:-10 degC ~ 50 degC.Humidity:10% ~

Working conditions	90%
Storage conditions	Temperature:-20 degC ~ 70 degC, Humidity:5% ~ 95%
Device name	Can be customized, letter and digital for option, at max 30 ASCII characters.
Password	Enter default pairing code "1234", it can be customized. At max 6 digitals.
Power plug dimension	3.5*1.1mm

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.



Соответствующие документы:

Хотите узнать больше о продукте?основ уверены, верны?пожалуйста Кликните сюда.

***Specification**

***Руководство по программе**

***Руководство пользователя**

***Драйвер для WINDOWS**

***Инструменты настройки параметров принтера**

***USB Printdemo(Демонстрация прикладного программного обеспечения)**

***Bluetooth Printdemo(Демонстрация прикладного программного обеспечения)**

***SDK для Android**

***CD файлы**