Обои для рабочего Всенаправленная считывания штрих-кодов (Модель: OCBS-T005)

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ:

Оперативный	
Источник света	650nm видимые лазерные диоды (VLD)
Глубина поля сканирования	0 - 200 мм (UPC / EAN 100%, PCS = 90%)
Схема сканирования	5 направления поля сканирования
Скорость сканирования	1400 сканирований в секунду (всенаправленный)
Количество строк развертки	20
Минимальная Штрих Ширина	5mil @ PCS 90%
Контраст печати	30% @ UPC / EAN 100%
Показатели (LED)	Двухцветный светодиод (синий и красный)
Звуковой сигнал	Программируемый тон и объем
Системные интерфейсы	Разрыв клавиатуры, RS-232C, HID USB
Физический	
Измерение	139mmX 105mmX 200 мм (ДхШхВ)
Вес	535g
Кабель Протяженность	2M
Тент	50 ° вперед
Мощность	
Входное напряжение	5 В постоянного тока ± 10%
Мощность	1.35 Вт
Рабочий ток	270mA @ 5V (обычный); 350 мА (макс.)
Окружающей среды	
Рабочая температура	0degree C-40degree C (32degree F - 104 степень F)
Температура хранения	-20degree C - 60 градусов C (-4 степень C - 140 степень F)
Влажность	5% ~ 90% RH, без конденсата
Уровень освещенности	До 4000 Lux (флуоресценция)
Оставьте Прочность	Разработанный, чтобы противостоять 1.0M падает до бетонной поверхности
Регулирующий	
Класс лазера	CDRH Класс IIa; IEC 60825-1: Класс I
EMC	CE EN55022 B FCC Part 15 Class B VCCI, BSMI

Описание товара:

Product Picture

Features

Simple but not easy

High performance 32 bit hardware decoding ;

NICAM power design, suitable for

noisy environments;

Multiple/Single line scanning capability, meet different requirement;

Multiple interfaces: PS/2, RS232 or USB

www.ocominc.com

All-round show

Parameter

Operational	
Light Source	650nm visible laser diodes (VLD)
Depth of Scan Field	0 - 200 mm (UPC/EAN 100%, PCS=90%)
Scan Pattern	5 directions of scan field
Scan Rate	1400 scans per second (omni-directional)
Number of Scan Lines	20
Minimum Barcode Width	5mil @ PCS 90%
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Two-color LED (blue & red)
Beeper Operation	Programmable tone and volume
System Interfaces	Keyboard wedge, RS-232C, HID USB
Physical	
Dimension	139mmX 105mmX 200mm (LxWxH)
Weight	535g
Cable Lenth	2M
Tilt	50° forward
Power	
Input Voltage	5VDC ± 10%
Power	1.35 W
Operating Current	270mA @ 5V (Normal); 350mA (Max)
Environmental	

Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°C - 140°F)
Humidity	5% ~ 90% RH, non-condensing
Light Levels	Up to 4000 Lux (fluorescence)
Drop Durability	Designed to withstand 1.0M drops to concrete surface
Regulatory	
Laser Class	CDRH Class IIa; IEC 60825-1: Class I
EMC	CE EN55022 B FCC Part 15 Class B VCCI, BSMI

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.
OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.
OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.
You can find more information of us at: www.ocominc.com,
Together we quest for the best.

Соответствующие документы:

Хотите знать больше о продукте information?Пожалуйста Нажмите здесь.

Спецификация