Высокая скорость сканирования Ручной USB Laser сканер штрих-кода машины (Модель: OCBs-L009)

Спецификация:

| Производительность Характеристика | | | | | |
|---|---|--|--|--|--|
| Источник Света: | | | | | |
| Скорость | 200 сканирований в второй | | | | |
| сканирования: | | | | | |
| ЦПУ | 32 бит | | | | |
| Чтение Расстояние | 2.5 ~ 600 мм (100% UPC / EAN) | | | | |
| Ширина сканирования | | | | | |
| Сканер Тип: | Двунаправленный | | | | |
| Операция режим | срабатывает | | | | |
| Разрешение: | 3mil высокое разрешение серии / 5mil долго глубина серии поле | | | | |
| Печать Контрастность | ность 30%, Минимальная разница отражающей | | | | |
| Минимум: | | | | | |
| Декодировать | UPC / EAN, UPC / EAN с дополнительным, UCC / EAN 128, Code 39, Code | | | | |
| Возможности: | 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Кода бар, с | | | | |
| | чередованием 2 из 5, Дискретная 2 из 5, Code 93, MSI, Код 11, RSS | | | | |
| | варианты, Китайский 2 из 5, MSI / Плесси, Великобритания / Плесси, | | | | |
| | UCC / EAN 128, китайский код, GS1 Бар данных (RSS) серии | | | | |
| Сканирование Угол | ± 65° (наклон); ± 60° (шаг); ± 42° (горизонтальный) | | | | |
| Физические Характери | | | | | |
| Интерфейсы | PS2, RS232, USB | | | | |
| Поддерживается: | | | | | |
| Напряжение: | 5V DC ± 5% | | | | |
| Ток: | 85 мА (операционная); 100 (макс) | | | | |
| Индикатор | Звуковой сигнал, LED | | | | |
| Материал | ABS + PC | | | | |
| Стоять | Необязательный | | | | |
| Размеры: | 156 * 68 * 83 мм (L * W * H) | | | | |
| Bec: | 235г | | | | |
| Цвет: | Серый и черный | | | | |
| Окружающая среда пол | пьзователя | | | | |
| Рабочая Температура: | 0 градусов C ~ 45 градусов C | | | | |
| Температура | -40 Градусов C ~ 60 градусов C | | | | |
| хранения: | | | | | |
| Влажность: | 5% -90% (без конденсата) | | | | |
| Электростатический | Соответствует +/- 15KV разряд воздуха и +/- 8 кВ контактной разряда | | | | |
| разряд: | | | | | |
| Окружающего | 0 ~ 100000 LUX | | | | |
| освещения | | | | | |
| Оставьте | Выдерживает многократные падения на 1,5 млн бетонной | | | | |
| характеристики: | поверхности | | | | |
| Классификация лазера EN60825-1, класс 1 | | | | | |

Подробнее:



Product Picture





Features

Simple but not easy

200scan/sec high scan rate and long reading distance;







Durable construction combined with future-proofing;









KBW, RS232 and USB supported;



All-round show







Parameter

| Performance Character | istics | | |
|---|--|--|--|
| Light Source: | 650nm visible | | |
| Scan Rate: | 200 scans per second | | |
| CPU | 32 bit | | |
| Reading Distance | 2.5 ~600mm (100% UPC/EAN) | | |
| Width of Scan | 50mm@60mm, 220mm@200mm | | |
| Scanner Type: | Bi-directional | | |
| Operation mode | triggered | | |
| Resolution: | 3mil high resolution series / 5mil long depth field series | | |
| Print Contrast Minimum: | 30%, minimum reflective difference | | |
| UPC/EAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, Code 38 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Coda bar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese code GS1 Data Bar (RSS) series | | | |
| Scanning Angle | ±65°(tilt); ±60°(pitch); ±42°(yaw) | | |
| Physical Characteristic | 8 | | |
| Interfaces Supported: | PS2, RS232, USB | | |
| Voltage: | 5V DC±5% | | |
| Current: | 85 mA (Operating); 100 (Max) | | |
| Indicator | Beeper, LED | | |

| Material | ABS+PC | | |
|--------------------------|---|--|--|
| Stand | Optional | | |
| Dimensions: | 156*68*83 mm (L*W*H) | | |
| Weight: | 235g | | |
| Color: | Grey and black | | |
| User Environment | | | |
| Operating Temperature: | 0 Degree C~45 Degree C | | |
| Storage Temperature: | -40 Degree C~60 Degree C | | |
| Humidity: | 5%-90% (non-condensing) | | |
| Electrostatic Discharge: | Conforms to +/-15KV air discharge and +/-8KV of contact discharge | | |
| Ambient Illumination | 0 ~ 100,000 LUX | | |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete surface | | |
| Laser classification | EN60825-1+ class 1 | | |

Production Line





Capacity

| Verified | Product Name | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| 1 | Thermal Printer | 40,000 Sets / Month | 250,000 Sets |
| 1 | Dot Matrix Printer | 15,000 Sets / Month | 10,000 Sets |
| 1 | Bluetooth Printer | 30,000 Sets / Month | 20,000 Sets |
| 1 | Barcode Scanner | 40,000 Sets / Month | 20,000 Sets |
| 1 | POS Machine | 5,000 Sets / Month | 10,000 Sets |
| 1 | Magnetic Card Reader and Writer | 45,000 Sets / Month | 50,000 Sets |

√ Indicates information has been verifed onsite by TUV on 2013.7.15

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfication.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products



have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

| Verified | Machine Name | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| 1 | Ageing Tester | No Information | 6 |
| 1 | Withstand Voltage Tester | CC2670A | 1 |
| 1 | Oscilloscope | TBS1102 | 1 |
| 1 | DC Power Supply | PS-305DM | 6 |
| 1 | Digital Torque Meter | HP100 | 1 |
| 4 | Calliper | GUANGLU | 2 |
| 1 | Multi-meter | VC890D | 7 |
| 1 | Test Computer | No Information | 13 |
| | | | |

7

vo information 13

✓ Indicates information has been verifed onsite by IUV on 2013.7.15

Certifications



Packing and Shipment





Payment

















Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand,

and we have estabilshed goods relationship with our customers and have friendly communication with each other.



Why you choose us?





Flexible Cooperation

Company Profile

This Assessed Supplier Has Been Independently Verified

Build Your Growth On Trust









OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.



Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;

Websites: http://www.possolution.com.cn; http://www.ocominc.com;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637,190852203; Tel/Fax: +86.755.8605.3207.



Соответствующие документы:

Спецификация Руководство пользователя