

Миниатюрный переносной сборщик данных для сбора данных POS Terminal (Модель: OCBS -D004)

Спецификация:

| | |
|----------------------------|---|
| Беспроводная связь: | |
| модуляция | GFSK |
| Скорость передачи | 200Kbps |
| Мощность | 10dBm |
| Дальность передачи | Визуальное расстояние прямой 300 метров |
| Антенна | Встроенная пружинная антенна |
| Технические характеристики | |
| Источник света | 650 нм лазер |
| Поддерживаемые штрих-коды | EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN128, Codaber, Industoal 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI и т. Д. |
| Тип сканера: | Двунаправленный |
| Скорость сканирования | 48 ± 2 сканирования / сек. |
| Расстояние сканирования | 10-520mm |
| Ширина сканирования | 20мм @ окно, 220мм @ 200мм |
| разрешение | 0.10mm (pcs0.9) |
| Глубина резкости | 0 ~ 250 мм (0,33 мм, PCS 90%) |
| Рабочий путь | Срабатывание по триггерному или автоматическому (непрерывному режиму) |
| Физические характеристики | |
| Память: | 1М (может хранить 30 000 штрих-кодов) |
| Интерфейсы: | Стандартный мини-USB-приемник конфигурации; RS232 и PS2 дополнительно |
| Текущий: | 96 мА (рабочий) 46 мА (в режиме ожидания) |
| Батарея: | Встроенная перезаряжаемая литиево-ионная батарея (3.7V, 1900mAh) |
| материал | ABS + PC |
| Размеры: | 102mmX46mmX28mm (сборщик данных) 52mmX20mmX10mm (приемник) |
| Вес: | 130 г (с батареей) |
| Пользовательская среда | |
| Рабочая Температура | -20 градусов С ~ 45 градусов С |
| Температура хранения | -20 градусов С ~ 60 градусов С |
| Влажность: | 5 ~ 95% относительной влажности, без конденсации |
| Безопасно | |
| EMI / RFI: | CE & Согласование FCC DOC |
| Стандарт безопасности | Второй национальный стандарт лазерной безопасности |
| Информация для заказа | |
| OCBS-D004 | 433MHZ Беспроводной мини-портативный контрольный терминал |
| OCBS -D104 | USB-кабель Мини-портативный контрольный терминал |

Информация о продукте:



ocom
All your side

**Wireless/USB cable
Mini Portable Stocktaking Terminal
OCBS-D004/OCBS-D104**



Product Picture



Features

Simple but not easy

Mini data collector,
convenient and portable;



Wireless version:
working distance can meet general
request, 30 to 300m in open area;



Instantly store and bulk transfer mode,
secure to keep the data;
Can store 30,000 barcodes;



Auto-turn-off at low voltage.
Settable standby time,
high efficiency and energy saving;



Easy and comfortable operation;



All-round show





Application Area

Commercial: handheld mobile POS, chains / stores / counters data acquisition, shoes ordering, card management, bill management

Commonality: mobile government, mobile police, population information management, postal management, library management

Logistics: warehouse management, product traceability, picking medicine distribution, logistics and express, logistics and distribution

Industry: production process management, forestry data collection, three meter reading, fixed asset management,



Parameter

| Wireless Communications: | |
|--------------------------|--|
| Modulation | GFSK |
| Transmission rate | 200Kbps |
| Power | 10dBm |
| Transmission Distance | Visual straight line distance 300 meters |
| Antenna | Built-in spring antenna |

| Performance Characteristics | |
|-----------------------------|---|
| Light Source | 650nm laser |
| Supported barcodes | EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN128, Codaber, Industoal 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI etc |
| Scanner Type: | BI-directional |
| Scan rate | 48±2 scan/second |
| Scan distance | 10-520mm |
| Scan width | 20mm@window, 220mm@200mm |
| Resolution | 0.10mm (pcs0.9) |
| Depth of Field | 0~250mm (0.33mm, PCS 90%) |
| Working Way | Triggered or automatic (continuous mode) scanning |
| Physical Characteristics | |
| Memory: | 1M (Can store 30,000 barcodes) |
| Interfaces: | Standard configuration mini USB receiver; RS232 and PS2 optional |
| Current: | 96mA (working) 46mA(standby) |
| Battery: | Built-in rechargeable lithium ion battery (3.7V, 1900mAh) |
| Material | ABS+PC |
| Dimension: | 102mmX46mmX28mm (Data Collector) 52mmX20mmX10mm (Receiver) |
| Weight: | 130g (with battery) |
| User Environment | |
| Operation Temperature | -20 Degree C~45 Degree C |
| Storage Temperature | -20 Degree C~60 Degree C |
| Humidity: | 5~95% relative humidity, non-condensing |
| Safe | |
| EMI/RFI: | CE & FCC DOC compliance |
| Safety Standard | The second national laser safety standards |
| Ordering Information | |
| OCBS-D004 | 433MHZ Wireless Mini Portable Stocktaking Terminal |
| OCBS-D104 | USB Cable Mini Portable Stocktaking Terminal |

Production Line





Capacity

| Verified | Product Name | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| ✓ | Thermal Printer | 40,000 Sets / Month | 250,000 Sets |
| ✓ | Dot Matrix Printer | 15,000 Sets / Month | 10,000 Sets |
| ✓ | Bluetooth Printer | 30,000 Sets / Month | 20,000 Sets |
| ✓ | Barcode Scanner | 40,000 Sets / Month | 20,000 Sets |
| ✓ | POS Machine | 5,000 Sets / Month | 10,000 Sets |
| ✓ | Magnetic Card Reader and Writer | 45,000 Sets / Month | 50,000 Sets |