

портативный Беспроводной сканер штрих

(Модель:OCBS-W700)

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ:

ФИЗИЧЕСКИЕ CHARACTERISTICS	
Источник света:	Видимый красный лазер 650 нм
Сканер Размеры:	160мм * 70мм * 40мм(Ш * В * Г)
Вес:	300G
Материал:	ABS + PC
Режим сканирования:	Один линия сканирования; Ручной / автоматический
Индикатор Путь:	Зуммер и индикатор света
ДЕЯТЕЛЬНОСТИ CHARACTERISTICS	
Ширина поля сканирования:	20mm @ сканер окно 260mm @ 260mm
Глубина поля сканирования:	4mil (0,1 мм) / 5-60мм 5mil (0,12 мм) / 10-100мм 10mil (0,25 мм) / 15-250мм 35mil (0.89мм) / 140-600мм 43mil (1.1мм) / 150-800мм
Скорость сканирования:	120 скан / сек
Сканирование Точность:	0.10 мм (PCS0.9)
Печать Контрастность:	Минимальная разница отражение 30%
Error Rate:	1 / (6million)
Расшифруйте возможность:	Международные общие 1D штрих-коды
Ток:	60 мА (рабочий); 5µА (режим ожидания)
Сканирование Corner:	32 °
Сканирование Высота:	68 °
Сканирование Угол Avertence:	52 °
Рабочая частота:	2,4
Расстояние связи:	100 м (Открытые места) 20м (в помещении)
Интерфейс связи:	USB
Пользовательская среда CHARACTERISTICS	
Падениям:	2м свободного падения
Лазерный уровень:	Уровень-1 стандарт лазерной безопасности
Зарядка мощность:	Постоянный ток5V

Описание товара:



Wireless Barcode Scanner

OCPP-W700

Product Picture





Features

Simple but not easy

Integrated non-volatile memory (can store about 500 barcodes);



Outside communication distance can



reach 100m, inside is 20m;;

20 scanners can work in the same field without interfering each other;



Plug and play;



800mA big capacity Li-battery.



||| All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Red Laser 650 nm
Scanner Dimensions(W * H * D)	160mm * 70mm * 40mm
Weight	300G
Material	ABS + PC
Scanning Mode	One line scanning; Manual / Automatic
Indicator Way	Buzzer and Indicator Light
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	20mm@scanner window 260mm@260mm
Depth of Scan Field	4mil (0.1mm)/5-60mm 5mil (0.12mm)/10-100mm 10mil (0.25mm)/15-250mm 35mil (0.89mm)/140-600mm 43mil (1.1mm)/150-800mm

Scan Speed	120 scans/sec
Scan Precision	0.10mm (pcs0.9)
Printing Contrast	Minimum 30% reflection difference
Error Rate	1/(6million)
Decode Capability	International general 1D barcodes
Current	60mA (working); \leq 5uA(standby)
Scanning Corner	32°
Scanning Elevation	68°
Scanning Angle of Avertence	52°
Working Frequency	2.4GHz
Communication Distance	100m (Open Places) 20m (Indoor)
Communication Interface	USB
USER ENVIRONMENT CHARACTERISTICS	
Drop Specification	2m free fall
Laser Level	Level-1 laser safety standard
Charge Power	5VDC

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



© 2012-2013 All rights reserved. | www.cominc.com



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



Соответствующие документы:

Хотите знать больше о продукте information?Пожалуйста Нажмите здесь.

[Спецификация](#)