

Мини портативный Android мобильный Bluetooth POS термопринтер квитанции

(Модель: ОСРР-М082)

Характеристики:

| | |
|---------------------------|---|
| Размеры (Ш x Г x В) | 98 x 103 x 45мм |
| вес | 280 г |
| цвет | черный |
| Эффективная ширина печати | 72 мм |
| метод печати | Тепловое линия печати |
| команда печати | ESC / POS совместимый набор команд |
| скорость печати | 90мм / сек |
| разрешение | 8 точек / мм (203DPI) |
| Печать шрифт | В 12x24 / 24x24 в |
| емкость колонки | 48 / 24columns |
| размер знака | 1,5 x 3,0 мм (ширина x высота) / 3.0x3.0mm (ширина x высота) |
| Размер бумаги | Диаметр 80,0 мм до ± 0.1mm x30.0 |
| Толщина бумаги | От 0,06 до 0,08 мм |
| Набор символов | Буквенно-цифровой / китайский текст |
| Интерфейс | USB, RS-232, Bluetooth (опционально) |
| вспышка | 256KB |
| Адаптер питания | 9В DC / 2А |
| Заряд батареи | DC / 2000 мА 7.4V; Батарея может оставаться в течение 4-5 дней, когда он полон сил, он может напечатать документ 120-150М |
| Другие особенности | Обнаружение бумаги, обнаружение мощности, вручную закрыть |
| Рабочие условия | Температура: -10degreeC~50degreeC Влажность: 10%~90% |
| Условия хранения | Температура: -20degreeC~70 degreeC Влажность: 5%~95% |
| Имя устройства | Может быть настроена для выбора букв и цифр до 30 ASCII символов. |
| пароль | По умолчанию Введите код сопряжения "1234"Она может быть настроена. Максимум 6 Digitals. |
| Размер штепсельной вилки | 3,5 * 1,1 мм |

| | P / N | Описание |
|-------------------------|-----------------|---|
| ИлиДеринг информация | OCPP-M082-BB | С Bluetooth и батареей, Supprot Android |
| | OCPP-M082-BB-AI | С Bluetooth и батареей, Supprot Android и IOS |
| | OCPP-M082-UB | С Barrery USB связи, |
| | OCPP-M082-U | USB связи, без BT, батареи |
| | OCPP-M082-B | Bluetooth связи без батареи |
| | OCPP-M082-UC | USB связи, с Автомобильное зарядное устройство |
| | OCPP-M082-BC | Связь Bluetooth с Автомобильное зарядное устройство |
| | OCPP-M082-C | Другое Customized |

Информация о продукте:





Features

Simple but not easy

Support Windows, Android,
or iPhone OS;



Bluetooth, USB and
RS232 communication.

Battery charge indicator, easy to know rest power.



Higher print speed 90mm/sec.



100km TPH Life.





Low power consumption
and large capacity
Lithium battery.

All-round show





Application Area

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation,
Warehouse management, Delivery, Illegal Parking Ticket,
Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm

Delivery



Restaurant



Bus / Taxi Receipt



Traffic Citation



| | |
|----------------------------------|---|
| Overall Dimension (W×D×H) | 98×103×45mm |
| Weight | 280g |
| Color | Black |
| Effective print width | 72mm |
| Print method | Thermal line printing |
| Print commands | ESC/POS/STAR compatible command set |
| Print speed | Up to 90mm/sec |
| Resolution | 8 dots/mm(203dpi) |
| Print font | 12x24/ 24x24 |
| Column capacity | 48 columns/24 columns |
| Character size | 1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(W x H) |
| Paper dimensions | 80.0±0.1mm x diameter 30.0mm |
| Paper thickness | 0.06 to 0.08mm |
| Character set | Alphanumeric/ Chinese Kanji ASCII Font A:12×24 Font B: 9x17 Korean code page 949 |
| Communication Interface | USB/RS-232, Bluetooth |
| Flash | 256KB |
| Power Adapter | 9V DC/1.5A |
| Battery Power | 7.4V DC/ 2000mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper |
| Other features | Paper detection, power detection, Manual shut down |
| | Temperature:-10 degC ~ 50 degC.Humidity:10% ~ |

| | |
|----------------------|---|
| Working conditions | 90% |
| Storage conditions | Temperature:-20 degC ~ 70 degC, Humidity:5% ~ 95% |
| Device name | Can be customized, letter and digital for option, at max 30 ASCII characters. |
| Password | Enter default pairing code "1234", it can be customized. At max 6 digitals. |
| Power plug dimension | 3.5*1.1mm |

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



Соответствующие документы:

- *[Specification](#)
- *[Руководство по программе](#)
- *[Инструкция по эксплуатации](#)
- *[Драйвер для WinXP Win2000 WinVista Win7 Win8-32bit](#)
- *[Драйвер для Win7 Win8-64bit](#)
- *[Драйвер для Linux](#)
- *[Параметры настройки принтера Инструменты](#)
- *[USB Printdemo\(Application Software демо\)](#)
- *[Bluetooth Printdemo\(Application Software демо\)](#)
- *[SDK для Android](#)
- *[CD файлы](#)