Auto Sense 1D ручной лазерный сканер штрих-кода с подставкой

(Модель: OCBS -LA06)

Спецификация:

Технические характеристики	
Источник света:	Видимый лазер (650-670 нм)
Скорость сканирования:	100 сканов в секунду
Расстояние чтения	2,5 ~ 600 мм (100% UPC / EAN)
Тип сканера:	Двунаправленный
Разрешение:	0,10 мм (4 мил) при PCS 0,9
Минимальный контраст печати:	20%, минимальная отражающая разница (@ 650 нм)
Возможность декодирования:	UPC / EAN, UPC / EAN с дополнениями, UCC / EAN128, код 39, код 39 полный ASCII, код 39 trioptic, код 128, код 128 полный ASCII, codabar, чередующийся 2 из 5, дискретный 2 из 5, код 93, MSI , код 11, ATA, варианты RSS, китайский 2 из 5 ...
Физические характеристики	
Поддерживаемые интерфейсы:	PS2, RS232, USB
Напряжение:	DC + 5V +/- 5%
Текущий:	100 мА
Холостой ток:	& lt; 40 мА
Источник питания:	Мощность хоста или внешний (RS232) источник питания
Угол сканирования	Наклон 45 ° Высота 60 °
Габаритные размеры:	L165,42 мм X W69,72 мм X H89,67 мм
Вес:	140 г (без подставки)
стенд	C
Цвет:	Слоновая кость и черный
Пользовательская среда	
Рабочая Температура:	0 ° C ~ 50 ° C
Температура хранения:	-40 ° C ~ 70 ° C
Влажность:	5 ~ 95% относительной влажности, без конденсации
Электростатический разряд:	Подтвердите сброс воздуха +/- 15KV и +/- 8KV контактного разряда
Технические характеристики:	Выдерживает несколько капель 1,5 м для бетона
Безопасно:	
EMI / RFI:	FCC Class A и CE
Безопасность лазера:	CDRH класс 2 лазерный продукт

Информация о продукте:

Product Picture

Features

Simple but not easy
Auto-Induction built in, green design
High scan rate and long reading

distance
Excellent decode capability
KBW, RS232 and USB supported

All-round show

Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5,discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	

Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0℃~50℃
Storage Temperature:	-40℃~ 70℃
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

www.ocominc.com

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

Monica Fu

OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China
Tel: 0086.755.8605.3207 ext 801
Fax: 0086.755.8605.3207 ext 868
Web: www.ocominc.com
E-mail: sales01@ocominc.com, sales01@ocomtech.com.cn
Skype: ocomsales01; **MSN**: ocomsales01@hotmail.com
Ali TM: cn1001868228; **QQ**: 1483705401
Mobile/Wechat/Whatsapp: 0086.189 4871 3992

Reliable One-Stop Supplier for POS and Auto-ID Related Products