Высококачественный сканер с частотой 433 МГц или Bluetooth с беспроводным кодом QR 2D штрих-код с подготовкой

Модель: ОКБС-в231-4/b

Функции:

- 1, 433 МГц беспроводная связь расстояние 300 м наружу, в помещении 100 м; Расстояние до беспроводной сети Bluetooth 20 м и 10 м в помещении;
- 2, оснащенные зарядкой и связью
- 3, мягкая пластмассовая крышка для защиты объектива и набросок значительно повышает эффективность антидемпинга;
- 4. можно сканировать штрих-коды на экране компьютеров и мобильных телефонов;
- 5, драйверы не требуются, Plug and Play;
- 6, может хранить более 10 000 единиц данных;
- 7, несколько сканеров могут быть подключены к одному приемнику (433 МГц).

Параметры:

Наличие источника света	617 Нм		
Освещение источника света	625 нм		
Угол сканирования	39 ° (h) 25 ° (v)		
Угол поворота	0-360 °		
Угол отсчета	65 °		
Угол наклона	60 °		
Контрастность печати	Более 25%		
1 d	СКП/МАКПТ, СКП/МАКПТ с дополнительными подсчетами, букландеан, ИССН, с купоном сек расширенным свободным коде128, GS1-128, исбт 128, код 39, код 39 Full ASCII, код 39 триоптик, код 93, код 32, коде11, Matrix 2 5, 2 из 5, дискретные 2оф 5, кодабар, MSI, 2, 5, барвариантс данные, ГС1, корейский 3 5, исбт Concat		
2D	Тип пдф417, микропдф417, сложные коды, нежно-39, матрица, максикоде, QR-код, ацтеков, микрокр		
Интерфейс	USB (кабельный приемник беспроводной связи)		
Диапазон связи	433 МГц: внутри: 100 м; Снаружи: 300 м (Макс.) Bluetooth: внутри: 10 м; Снаружи: 20 м (Макс.)		
Рабочая температура	-10 градусов с-45 градусов с		
Температура хранения	-20 ° c-65 ° c		
Влажность	5-85%		
Содержание влаги во время хранения	5%-95%		
Долговечность	Может выдержать целый ряд от 1,5 м до бетона		
Ввод питания	5 в DC, 280мА		
Время зарядки	6 ч.		
Батареи	1500мах		

Яркости	Внутри: 3 000 люкс Макс; Солнечный свет: Макс 86000 Люкс					
Класс IP	Ип42					
Диапазоны декодирования						
Типичная производительность *		Типовые рабочие диапазоны				
		Диапазон фокусировки HD				
Тип штрих-кода	Плотность обозначений	Ближайшем	Много			
Код 39	5,0 миль	5 мм	90 мм			
100% упка штрихкодов	13,0 миль	8 мм	200 мм			
Код 39	20,0 миль	8 мм	250 мм			
PDF 417	6,8 миль	5 мм	95 мм			
Матрица данных	10,0 миль	5 мм	110 мм			
QR-код для	20,0 миль	10 мм	150 мм			
Резолюция 1 d код 39	4 млн.					
Разрешение матрицы 2D данных	10 млн.					
Материала	АБС + РС					
Измерение	Сканер (70 * 95 * 168 мм), база (145 * 112 * 74 мм)					
Вес нетто	Сканер 185 g основание 186 g					
Сведения о заказе:	ОКБС-в231-4: 2D сканер штрихкодов беспроводной 433 МГц с колыбели					
	ОКБС-в231-b: 2D сканер с гнездом барокде Bluetooth					



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE











LONG DISTANCE WIRELESS COMMUNICATION

CHARGING CRADLE

NO NEED DRIVER, PLUG AND PLAY

STRONG DECODING ABILITY

STABLE STRUCTURE



FAST SCAN, HIGH RECOGNITION RATE





3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION





STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE





NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION, RICH TYPE OF DECODING

It'S APPLICATED AT ANY PLACE, THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT INORMATION

Aiming Light Source	617 nm LED		
Lighting Light Source	625 nm LED		
Scanning Angle	39° (H) x 25° (V)		
Rotation Angle	0 - 360°		
Elevation Angle	± 65°		
Tilt Angle	± 60°		
Print Contrast	Higherthan 25%		
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Barvariants, Korean 3 of 5, ISBT Concat		
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec		
Interface	USB (Wirelless receiver cable)		
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)		
Operating Temperature	-10 deg C - 45 deg C		
Storage Temperature	-20 deg C - 65 deg C		
Operating Humidity	5%-85%		
Storage Humidity	5%-95%		
Durability	With stands multiple 1.5m drops to concrete		
Input Power	DC 5V, 280mA		
Charging time	6h		
Battery	1500mAh		
Lumination	In side: 3.000 LUX max; Outside sunlight: 86000LUX max		
IP Grade	IP42		

DECODE RANGES					
Typical Performance*		Typical Working Ranges HD Focus Range			
				Bar Code Type	Symbol Density
Code 39	5.0 mil	5mm	90 mm		
100% UPCA	13.0 mil	8mm	200mm		
Code 39	20.0 mil	8mm	250mm		
PDF 417	6.8 mil	5mm	95mm		
Data Matrix	10.0 mil	5mm	110mm		
QR Code	20.0 mil	10 mm	150mm		
Resolution 1D Code 39	4 mil				
Resolution 2D Data Matrix	10 mil				
Material	ABS+PC				
Dimension	Scanner (70*95*168mm)	Base(145*112*74mm)			
Net Weight	Scanner 185g Base 186g				
Ordering Info.	433MHz wireless communication (OCBS-W231-4)				
	Bluetooth communication (OCBS-W231-B)				

Shipping and payment

- Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
- 2. EXPRESS: around 3-7 working days to arrive
- INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
- By sea: depend on which destination port
- 5. T/T
- Western Union
- 7. Escrow
- L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.













Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan

District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com Tel: 0086.755.86053207-815; Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: ocomsales15;

Whatsapp: +0086.189.4879.9080;