

## OCBS -W232 Портативный Bluetooth QR 2d CMOS сканер штрих-кода

| PHYSICAL CHARACTERISTICS       |                                                          |
|--------------------------------|----------------------------------------------------------|
| Light Source                   | Visible Laser Diode (VLD) @ 650 nm                       |
| scanner Dimensions(W * H * D)  | 168*72*93 mm                                             |
| receiver Dimensions(W * H * D) | 130*75*129mm                                             |
| Material                       | ABS+TPU /Aluminium alloy                                 |
| scanner Weight                 | 190g (Including battery)                                 |
| receiver Weight                | 180g                                                     |
| User Mode                      | Hand-held                                                |
| Scanning Mode                  | Manual/ Automatic                                        |
| Indicator Light                | Scanner LED Red and Blue receiver Left Green+ right Blue |
| Buzzer                         | Buzzer Volume Adjustable                                 |

| PERFORMANCE CHARACTERISTICS |                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Width of Scan Field         | 60mm@30mm ( From engine face )<br>98mm@100mm ( from engine face )                                                                                                                                                                                                                                                                                                                                                                 |
| Depth of Scan Field         | 10-450mm ( Contrast 0.9 Density0.25)                                                                                                                                                                                                                                                                                                                                                                                              |
| Scan Speed                  | 300 scans/sec                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Scan Precision              | 0.10-0.825mm                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Bit Error Rate              | 1/(5million)                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Symbolologies Supported     | 1D <u>UPC-A</u> , <u>UPC-E</u> , <u>EAN-8</u> , <u>EAN-13</u> Code 39, Code 32, Coda bar ,Code 128, ISBT 128, Code 93, Interleaved 2 of 5 Discrete 2 of 5 ,CODE11, MSI,  名称sey GS1-DataBar, UCC/EAN-128,BooklandEAN, Bookland EAN/ISBN , Trioptic Code39, CouponCodeGS1, DataBar-14, SETUP128 GS1Data Bar Limited, GS1Data Bar Expanded, RSS |
|                             | 2D <u>PDF417</u> <u>DataMatrix(DM)</u> QR                                                                                                                                                                                                                                                                                                                                                                                         |
| Battery                     | 3.7V/1200mAh,Li-ion                                                                                                                                                                                                                                                                                                                                                                                                               |
| Charge Time                 | 2.5 Hours                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Scan Time                   | 10 Hours                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Scan Current                | 95mA                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Standby current             | 25mA                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Maximum Pitch Angles        | 60°                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Maximum Tilt Angles         | 45°                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Working Frequency           | 433MHz                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Communication Distance      | 200m (Open Places)                                                                                                                                                                                                                                                                                                                                                                                                                |
| Flash                       | 16MB                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Communication Interface     | USB                                                                                                                                                                                                                                                                                                                                                                                                                               |