

Electronic cash register machine couter

(M/N:POS-8618)

Features:

pos system touch screen,cash register counter,electronic cash register machine

Intel Celeron 1037U dual core 1.8GHZ

HardDriverSSD32GB (default),SSD 64GB and HDD320G for optional

5 wireresistive touch screen(default),Capacitive screen for optional

Cardreader and VFD customer display for optional

I/OInterface Panel is hidden

Applications:

pos system touch screen,cash register counter,electronic cash register machine

Catering:hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer:Business Street, boutique, department store, cosmetics shop and high-classbarbershop

Recreation:sauna, spa, night club, theme park, casino and point of sales for lotteryticket

Commercial:information management terminals for parking lot, inn, aviation, subway,station and wharf

Pictureshow:

pos system touch screen,cash register counter,electronic cash register machine

| | | | |
|---|--|---|--|
| ✘ | | ✘ | |
| ✘ | | ✘ | |

Parameter:

pos systemdual screen, touch screen pos terminal, pos touch screen

| | |
|----------------------|--------------------------------------|
| Model | POS8618 |
| Optional Color | Black or White |
| Optional Peripherals | VFD220E |
| Main Board | Intel Celeron Processor |
| CPU | Intel Celeron 1037U dual core 1.8GHZ |
| Chipset | Intel NM70 |
| Memory Support | DDRIII 1066/1333*1 2GB (default) |

| | |
|---------------------------|---|
| Hard Driver | SSD32GB (default) |
| LCD panel Size | 15 inch TFT LCD |
| Brightness | 350cd/m2 |
| Resolution | 1024*768(max) |
| Touch Screen | 5 wire resistive touch screen |
| View Angle | Horizon: 150; Vertical :140 |
| I/O port | 1* power button 12V DC in jack*1 PS2KB/MS*1 Serial*1 DB9 male Parallel:1*DB25 Parallel port VGA(15Pin D-sub)*1 LAN:RJ-45*1 USB(2.0)*6 Audio out*1 MIC IN*1 |
| Operating temperature | 0°C to 40°C |
| Storage temperature | -20°C to 60°C |
| Compliance | FCC Class A/CE Mark/LVD/CCC |
| Packing dimension/ Weight | 410*310*410mm / 7.6 KGS |
| Operating System | Windows XP above, Embedded, WEPOS, Linux |
| Power adapter | 110-240V/50-60HZ AC power, Input DC12/5A out put |

Product Details:

possystem dual screen, touch screen pos terminal, pos touch screen

